



## TECHNICAL DATA SHEET

TDS 01.002

### Product

### CEBOFIX R

### Description

CEBOFIX R is a white, water based, acrylic fixative with quartz sands. It is used for substrate preparation for interiors and exteriors. CEBOFIX R has a white appearance and a slightly rough texture which improve the application, the coverage and uniform the chromatic harmony of the following coats of Cebos finishes. Due to its good permeability to water vapour it is especially recommended for the application of lime based products of the CeboArt range.

CEBOFIX R is available in 1 litre, 5 litres, 10litres containers.

### Surface treatment of the substrate

It can be applied over substrates based on gypsum, lime or cement fine rendered mortar, properly restored and free from dust and foreign substances.

### Colouring

CEBOFIX R can be coloured with CeboColorStation tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

### Application

CEBOFIX R can be applied by roller or brush, diluted with 20-30% water, in one or more coats according to the absorption of the substrate. Wait until the product is completely dry (minimum 24 hours) before the application of the chosen Cebos finish.

### Useful suggestions

### VOC Classification (2004/42/CE Directive)

Product category: Binding primers (h).  
Maximum VOC content limit value (2010) for the ready-to-use product: 30 g/l.  
CEBOFIX R contains: 8 g/l VOC

### Technical characteristics

Estimated Coverage: 10-12 m<sup>2</sup>/litre per coat.  
Appearance: liquid  
Specific weight: 1.53 g/cm<sup>3</sup>  
pH: 8.5 - 9  
Drying time: 4-6 hours between coats; complete drying after at least 24 hours according to ambient temperature and relative humidity.

### Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

### Safety warnings

CEBOFIX R does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately and show the safety data sheet of the product.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.