



TECHNICAL DATA SHEET

TDS 03.005

Product

CEBOIDEA

Description

CEBOIDEA is a water based acrylic paint that due to its particular formulation can be applied as a decorative coating to create special effects slightly in relief. The final effect is then enhanced by the following application of Cebos finishing paints.

CEBOIDEA is available in 1 litre, 5 litres, 10 litres containers.

Surface treatment of the substrate

It can be applied over all smooth substrates such as gypsum, levelling putty, even if slightly rough. Clean and level if necessary the surface, then apply CEBOFIX M transparent fixative based on an acrylic micro-emulsion. CEBOFIX M is specifically indicated in case of pulverulent surfaces, it must be applied by brush, in one coat, diluted 1:1 with water.

Colouring

CEBOIDEA shall not be coloured.

Application

CEBOIDEA is ready to use and can be applied by brush.

Apply the product in a uniform and homogenous layer of 2-3 mm and give the desired texture when the product is still wet, by means of the selected tool (rag-stippling trowel, brush, trowel or other decorative tools).

After about 6-8 hours, or in any case when the product is completely dry, apply the final chosen finish: CeboStyle Antico, CeboSi Setoso, Cebosi Riflessi, CeboSi Universal.

BARKODE Effect: On the prepared surface apply CEBOIDEA with a medium size brush, in a uniform thickness of 2-3 mm. Decorate the product with the appropriate tool CeboBars (cod. A/16) to attain vertical or horizontal stripes. When the product is still humid lightly smoothen the decoration with the trowel Caress (cod. A/38). It is advisable to carry out the application and following decoration procedure in areas of 1 meter width at a time.

Wait until the product is completely dry (6 – 8 hours); if necessary sandpaper the surface to remove all imperfections. Apply CeboStyle Antico and Cebolron in the desired colours and following the instructions on the relative Technical Data Sheets.

Useful suggestions

Working and drying time is variable according to the ambient temperature and relative humidity as well as the thickness of product applied.

VOC Classification (2004/42/CE Directive)

Product category: Interior matt walls and ceilings (a)

Maximum VOC content limit value (2010) for the ready-to-use product: 30 g/l.

CEBOIDEA contains: 11 g/l VOC

Technical characteristics

Estimated Coverage: 2-3 m²/lt according to the method of application and desired texture.

Appearance: paste

Specific weight: 1.34 g/cm³

pH: 8.5 – 9

Drying time: 6-8 hours according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOIDEA does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately and show the safety data sheet of the product.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.