



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Review n.1
Date: 01/03/2011

TECHNICAL DATA SHEET

TDS 04.002

Product

CEBOTOP GLASS

Description

CEBOTOP GLASS is a transparent, gloss washable decorative finish for interiors, based on acrylic resins.

CEBOTOP GLASS is available in 1 litre containers.

Surface treatment of the substrate

It is applied, without dilution on surfaces prepared with CEBOTOP FONDO, to reach the desired decoration.

Colouring

CEBOTOP GLASS shall not be coloured.

Application

CEBOTOP GLASS is ready-to-use and it is applied with a sea-sponge or rag stippler, according to the required aesthetic effect.

With the aid of a palette, pour a small quantity of CEBOTOP GLASS on a side; dip the chosen and damp tool into the product; on the free side of the palette to empty the tool from the excess of product and proceed with the decoration by dabbing the surface.

Useful suggestions

VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)
Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.
CEBOTOP GLASS contains: 27 g/l VOC

Technical characteristics

Estimated Coverage: 20 m²/litre
Appearance: liquid
Specific weight: 1.05 g/cm³
pH: 8 – 9
Resistance to washing: The product withstands ordinary cleaning maintenance.
Drying time: 4-6 hours according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOTOP GLASS does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.