



TECHNICAL DATA SHEET

TDS 04.005

Product

CEBOSI UNIVERSAL

Description

CEBOSI UNIVERSAL is a matt, semi-hiding, washable, water based finish for interiors and exteriors; the ideal product to create soft shaded effects of ancient times.

CEBOSI UNIVERSAL is available in 1 litre and 5 litres containers.

Surface treatment of the substrate

It can be applied over all substrates such as gypsum, lime or cement based fine render. According to the final effect desired, different products for the preparation of the substrate are required. See the entry *Application*.

Colouring

CEBOSI UNIVERSAL can be coloured with CeboColorStation tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

Application

Application over CEBOSI FONDO

Carefully clean the surface and, if necessary, repair and level the substrate. Apply CEBOSI FONDO in the same colour of CEBOSI UNIVERSAL with a short pile roller, in one or two coats to reach a perfect cover of the substrate. In case of substrates which are highly absorbent, give a first coat of CEBOSI FONDO diluted 30% with water.

Wait until the surface is completely dry (after about 6-8 hours).

CEBOSI UNIVERSAL is ready-to-use and must be applied in one coat with the appropriate CeboSi brush (available in 2.5" and 4" size): apply on the surface with crossed brush-strokes avoiding clear-cut squaring and overlapping of product.

CEBOSI UNIVERSAL can also be applied with a woollen glove applying the non-diluted product in uniform, circular movements keeping the hand flat and light.

Application over CEBOSTONE:

On the properly treated substrate apply CEBOSTONE in the same colour of CEBOSI UNIVERSAL, diluted with maximum 5% water, with a medium size flat brush in crossed directions.

Wait until the surface is completely dry (after about 6-8 hours).

CEBOSI UNIVERSAL is ready-to-use and must be applied in one coat with the appropriate CeboSi brush (available in 2.5" and 4" size): apply on the surface with crossed brush-strokes avoiding clear-cut squaring and overlapping of product.

Useful suggestions

It is possible to add to CEBOSI UNIVERSAL the coloured flecks CEBOARD: refer to the relative Colour Guides for the combination of colours and the complete application cycle.

VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)

Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.

CEBOSI UNIVERSAL contains: 33 g/l VOC

Technical characteristics

Estimated Coverage: 6 – 10 m²/litre, in two coats, according to the method of application and type of finish chosen.

Appearance: liquid

Specific weight: 0.97 g/cm³

pH: 8.5 – 9

Resistance to washing: The product withstands ordinary cleaning maintenance.

Drying time: 4-6 hours according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOSI UNIVERSAL does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.