



# TECHNICAL DATA SHEET

TDS 04.027

## Product

## CEBOFREE

## Description

CEBOFREE is a water based, multicolour finish for interiors, available in WHITE and BLACK. Easy to apply and very versatile, CEBOFREE is the ideal solution for all rooms: its coloured flecks give the possibility to create various effects with shaded tones and slightly contrasts reliefs.

CEBOFREE WHITE combines with the additives CEBOAD, CEBOUP and CEBODREAM, to attain polychromatic effects in gold and silver tone.

CEBOFREE BLACK combines with CEBOSTYLE ANTICO and the additive CEBODREAM, to attain a metallic and sparkling effect.

CEBOFREE, in both types, is available in 1.6 litres and 4 litres containers.

## Surface treatment of the substrate

It can be applied over all substrates such as gypsum, lime or cement based fine render. Carefully clean the substrate. If necessary repair or level the surface, then apply two coats of FONDOPLUS by roller, diluted with 10% water.

Use FONDOPLUS white when applying CEBOFREE WHITE.

Use FONDOPLUS col. 252/1 when applying CEBOFREE BLACK.

## Colouring

CEBOFREE can be coloured with CeboColorStation tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

## Application

Apply CEBOFREE in one coat, without dilution, with the appropriate CeboSi 2.5" brush: dip the brush into the product and apply on the surface with crossed brush-strokes. After having applied 4-6 m<sup>2</sup>, and in any before the complete drying of the product, go over the painted surface with the special plastic spatula CARESS (cod. A/38) pressing lightly.

Refer to the specific colour cards to choose the required combination with CEBOSTYLE ANTICO basis and the selection of the metallic additives CEBOUP and CEBODREAM.

## Useful suggestions

## VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)

Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.

CEBOFREE contains: 30 g/l VOC

## Technical characteristics

Estimated Coverage: 8 m<sup>2</sup>/litre

Appearance: dense liquid

Specific weight: 1.03 g/cm<sup>3</sup>

pH: 7 – 7.5

Resistance to washing: The product withstands ordinary cleaning maintenance.

Drying time: 6-8 hours according to ambient temperature and relative humidity.

## Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

## Safety warnings

CEBOFREE does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.