



TECHNICAL DATA SHEET

TDS 04.031

Product

CEBOTIME

Description

CEBOTIME is an acrylic, water based, washable finish for interiors. Thanks to its delicate satin appearance it is possible to create refined decorations. The one-coat application consents to optimize the working time, ensuring at the same time a high surface resistance. Moreover, the shine of the pigment in the base gives the possibility to attain very clear and bright colours.

CEBOTIME is available in 1 litre, 3 litres, 5 litres and 10 litres containers.

Surface treatment of the substrate

It can be applied on all substrates as long as suitably prepared. The surface must be perfectly clean, dry and uniform. In case of new or recently repaired walls, highly absorbent or chalky substrates, carefully clean the surface and apply by paintbrush one coat of transparent fixative CEBOFIX M, diluted 1:1 with water.

Then apply one or two coats of white, acrylic base coat for interiors FONDOPLUS with a short hair woollen roller, diluted with 10% water until the surface is entirely covered. CEBOTIME must be applied when FondoPlus is completely dry (after about 6-8 hours).

Colouring

CEBOTIME can be coloured with CeboColorStation tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

Application

CEBOTIME is ready-to-use and it must be applied in one coat with the appropriate CeboSi paintbrush, available in 2.5 and 4 inches size: dip the brush into the product and paint in crossed brush-strokes avoiding clear-cut squaring. Continue the application to reach the already painted area with the empty brush, in order to avoid noticeable overlapping of colour.

Useful suggestions

VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)
Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.
CEBOTIME contains: 30 g/l VOC

Technical characteristics

Estimated Coverage: 10 m²/litre according to the type of finish required.
Appearance: liquid
Specific weight: 1.15 g/cm³
pH: 8 – 9
Resistance to washing: The product withstands ordinary cleaning maintenance.
Drying time: 4-6 hours according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOTIME does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.