

## Safety data sheet

### SECTION 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Code: **S.S. 01.001**  
Product name: **CeboFondo**

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Lime putty based rendering coat, for interiors and exteriors.**

#### 1.3. Details of the supplier of the safety data sheet

Name: **Cebos Color S.r.l.**  
Full address: **Via Dei Dossi n. 7**  
District and Country: **24040 OSIO SOPRA (BG)**  
**ITALY**  
Tel. (+39) 035 265141  
Fax (+39) 035 2651431

e-mail address of the competent person  
responsible for the Safety Data Sheet  
Product distribution by

**carlo@cebos.it**  
**Cebos Color S.r.l.**

#### 1.4. Emergency telephone number

For urgent inquiries refer to

**Contact your local poison information service;**  
**Technical information: Cebos Color Tel. (+39) 035 265141 (Lun-Ven 8.30/12.30 -**  
**13.30/18.00)**

### SECTION 2. Hazards identification.

#### 2.1. Classification of the substance or mixture.

The product is classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of EC Regulation 1907/2006 and subsequent amendments. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Serious eye damage, category 1

H318

Causes serious eye damage.

#### 2.2. Label elements.

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.



**S.S. 01.001 - CeboFondo**

Signal words: Danger

## Hazard statements:

**H318** Causes serious eye damage.

## Precautionary statements:

**P101** If medical advice is needed, have product container or label at hand.  
**P102** Keep out of reach of children.  
**P280** Wear protective gloves / protective clothing / eye protection / face protection.  
**P302+P352** IF ON SKIN: wash with plenty of water / . . .  
**P305+P351+P338** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
**P313** Get medical advice / attention.

**Contains:** CALCIUM HYDROXIDE

**2.3. Other hazards.**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**SECTION 3. Composition/information on ingredients.****3.1. Substances.**

Information not relevant.

**3.2. Mixtures.**

Contains:

Identification.	Conc. %.	Classification 1272/2008 (CLP).
<b>CALCIUM HYDROXIDE</b>		
CAS. 1305-62-0	6 - 7	Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335
EC. 215-137-3		
INDEX. -		
<b>ETHANOLAMINE</b>		
CAS. 141-43-5	0 - 0,05	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Corr. 1B H314, STOT SE 3 H335
EC. 205-483-3		
INDEX. 603-030-00-8		

Note: Upper limit is not included into the range.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**SECTION 4. First aid measures.**

**S.S. 01.001 - CeboFondo**

**4.1. Description of first aid measures.**

**EYES:** Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

**SKIN:** Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

**INGESTION:** Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

**INHALATION:** Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

**4.2. Most important symptoms and effects, both acute and delayed.**

For symptoms and effects caused by the contained substances, see chap. 11.

**4.3. Indication of any immediate medical attention and special treatment needed.**

Information not available.

**SECTION 5. Firefighting measures.**

**5.1. Extinguishing media.**

**SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

None in particular.

**5.2. Special hazards arising from the substance or mixture.**

**HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products.

**5.3. Advice for firefighters.**

**GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

**SECTION 6. Accidental release measures.**

**6.1. Personal precautions, protective equipment and emergency procedures.**

**S.S. 01.001 - CeboFondo**

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

**6.2. Environmental precautions.**

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

**6.3. Methods and material for containment and cleaning up.**

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Check incompatibility for container material in section 7. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

**6.4. Reference to other sections.**

Any information on personal protection and disposal is given in sections 8 and 13.

**SECTION 7. Handling and storage.**

**7.1. Precautions for safe handling.**

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

**7.2. Conditions for safe storage, including any incompatibilities.**

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

**7.3. Specific end use(s).**

Information not available.

**SECTION 8. Exposure controls/personal protection.**

**8.1. Control parameters.**

Regulatory References:

DEU	Deutschland	MAK-und BAT-Werte-Liste 2012
ESP	España	INSHT - Límites de exposición profesional para agentes químicos en España 2015

**S.S. 01.001 - CeboFondo**

FRA	France	JORF n°0109 du 10 mai 2012 page 8773 texte n° 102
GRB	United Kingdom	EH40/2005 Workplace exposure limits
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81
POL	Polska	ROZPORZĄDZENIE MINISTRA PRACY I POLITYKI SPOŁECZNEJ z dnia 16 grudnia 2011r
EU	OEL EU	Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC.
	TLV-ACGIH	ACGIH 2014

**CALCIUM HYDROXIDE**

**Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min	
		mg/m3	ppm	mg/m3	ppm
VLA	ESP	5			
VLEP	FRA	5			
WEL	GRB	5			
NDS	POL	2			
OEL	EU	5			
TLV-ACGIH		5			

**ETHANOLAMINE**

**Threshold Limit Value.**

Type	Country	TWA/8h		STEL/15min		
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	5,1	2	10,2	4	SKIN.
MAK	DEU	5,1	2	10,2	4	
VLA	ESP	2,5	1	7,5	3	SKIN.
VLEP	FRA	2,5	1	7,6	3	SKIN.
WEL	GRB	2,5	1	7,6	3	SKIN.
TLV	ITA	2,5	1	7,6	3	SKIN.
NDS	POL	2,5		7,5		
OEL	EU	2,5	1	7,6	3	SKIN.
TLV-ACGIH		7,5	3	15	6	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

**8.2. Exposure controls.**

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

**HAND PROTECTION**

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration

**S.S. 01.001 - CeboFondo**

and type of use.

**SKIN PROTECTION**

Wear category I professional long-sleeved overalls and safety footwear (see Directive 89/686/EEC and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

**EYE PROTECTION**

Wear a hood visor or protective visor combined with airtight goggles (see standard EN 166).

**RESPIRATORY PROTECTION**

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

**ENVIRONMENTAL EXPOSURE CONTROLS.**

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

**SECTION 9. Physical and chemical properties.**

**9.1. Information on basic physical and chemical properties.**

Appearance	pasty
Colour	white
Odour	characteristic
Odour threshold.	Not available.
pH.	> 10
Melting point / freezing point.	Not available.
Initial boiling point.	Not available.
Boiling range.	Not available.
Flash point.	> 60 °C.
Evaporation Rate	Not available.
Flammability of solids and gases	Not available.
Lower inflammability limit.	Not available.
Upper inflammability limit.	Not available.
Lower explosive limit.	Not available.
Upper explosive limit.	Not available.
Vapour pressure.	Not available.
Vapour density	Not available.
Relative density.	1,830 Kg/l
Solubility	partially soluble in water
Partition coefficient: n-octanol/water	Not available.
Auto-ignition temperature.	Not available.
Decomposition temperature.	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidising properties	Not available.

**9.2. Other information.**

VOC (Directive 2010/75/EC) :	2,00 % - 21,00 g/litre.
VOC (volatile carbon) :	0,87 % - 8,70 g/litre.

## SECTION 10. Stability and reactivity.

### 10.1. Reactivity.

There are no particular risks of reaction with other substances in normal conditions of use.

### 10.2. Chemical stability.

The product is stable in normal conditions of use and storage.

### 10.3. Possibility of hazardous reactions.

No hazardous reactions are foreseeable in normal conditions of use and storage.

ETHANOLAMINE: can react dangerously with: acrylonitrile, chloroepoxypropane, chlorosulphuric acid, hydrogen chloride, iron-sulphur compounds, acetic acid, acetic anhydride, mesityl oxide, nitric acid, sulphuric acid, strong mineral acids, vinyl acetate, cellulose nitrate.

### 10.4. Conditions to avoid.

None in particular. However the usual precautions used for chemical products should be respected.

ETHANOLAMINE: avoid exposure to air and sources of heat.

### 10.5. Incompatible materials.

ETHANOLAMINE: iron, strong acids and strong oxidising agents.

### 10.6. Hazardous decomposition products.

ETHANOLAMINE: nitrogen oxides, carbon oxides.

## SECTION 11. Toxicological information.

### 11.1. Information on toxicological effects.

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification. It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

This product may cause serious ocular lesions, cornea opacity, iris lesions, irreversible eye coloration.

CALCIUM HYDROXIDE  
LD50 (Oral).7340 mg/kg Rat

## SECTION 12. Ecological information.

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

### 12.1. Toxicity.

Information not available.

### 12.2. Persistence and degradability.

#### ETHANOLAMINE

Solubility in water. mg/l 1000 - 10000

Rapidly biodegradable.

#### CALCIUM HYDROXIDE

Solubility in water. mg/l 1000 - 10000

### 12.3. Bioaccumulative potential.

#### ETHANOLAMINE

Partition coefficient: n-octanol/water. -2,3

### 12.4. Mobility in soil.

#### ETHANOLAMINE

Partition coefficient: soil/water. -0,5646

### 12.5. Results of PBT and vPvB assessment.

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

### 12.6. Other adverse effects.

Information not available.

## SECTION 13. Disposal considerations.

### 13.1. Waste treatment methods.

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.



**CONTAMINATED PACKAGING**

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**SECTION 14. Transport information.**

**14.1. UN number.**

Not applicable.

**14.2. UN proper shipping name.**

Not applicable.

**14.3. Transport hazard class(es).**

Not applicable.

**14.4. Packing group.**

Not applicable.

**14.5. Environmental hazards.**

Not applicable.

**14.6. Special precautions for user.**

Not applicable.

**14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code.**

Information not relevant.

**SECTION 15. Regulatory information.**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture.**

**S.S. 01.001 - CeboFondo**

Seveso category. None.

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006.

Product.  
Point. 3

Substances in Candidate List (Art. 59 REACH).

None.

Substances subject to authorisation (Annex XIV REACH).

None.

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None.

Substances subject to the Rotterdam Convention:

None.

Substances subject to the Stockholm Convention:

None.

Healthcare controls.

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

Product not intended for uses provided for by Dir. 2004/42/CE.

**15.2. Chemical safety assessment.**

No chemical safety assessment has been processed for the mixture and the substances it contains.

**SECTION 16. Other information.**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

<b>Acute Tox. 4</b>	Acute toxicity, category 4
<b>Skin Corr. 1B</b>	Skin corrosion, category 1B
<b>Eye Dam. 1</b>	Serious eye damage, category 1
<b>Skin Irrit. 2</b>	Skin irritation, category 2
<b>STOT SE 3</b>	Specific target organ toxicity - single exposure, category 3
<b>H302</b>	Harmful if swallowed.
<b>H312</b>	Harmful in contact with skin.
<b>H332</b>	Harmful if inhaled.

**S.S. 01.001 - CeboFondo**

<b>H314</b>	Causes severe skin burns and eye damage.
<b>H318</b>	Causes serious eye damage.
<b>H315</b>	Causes skin irritation.
<b>H335</b>	May cause respiratory irritation.

**LEGEND:**

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

**GENERAL BIBLIOGRAPHY**

1. Regulation (EU) 1907/2006 (REACH) of the European Parliament
  2. Regulation (EU) 1272/2008 (CLP) of the European Parliament
  3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
  4. Regulation (EU) 2015/830 of the European Parliament
  5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
  6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
  7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
  8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
  9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- The Merck Index. - 10th Edition
  - Handling Chemical Safety
  - INRS - Fiche Toxicologique (toxicological sheet)
  - Patty - Industrial Hygiene and Toxicology
  - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
  - ECHA website

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.  
This document must not be regarded as a guarantee on any specific product property.  
The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.  
Provide appointed staff with adequate training on how to use chemical products.

Changes to previous review:



Cebos Color Srl  
24040 Ciso Sopra (BG)  
Via dei Dossi, 7  
Tel. +39 035 265141  
Fax +39 035 2651431  
C.F. & P.Iva 02567630161  
info@cebos.it  
www.ceboscolor.it

**Cebos Color S.r.l.**

Revision nr. 4

Dated 06/04/2016

Printed on 06/04/2016

Page n. 12/12

**S.S. 01.001 - CeboFondo**

The following sections were modified:  
01 / 02 / 03 / 08 / 12 / 14.