



TECHNICAL DATA SHEET

TDS 01.005

Product	CEBOFIX EXTRA
Description	<p>Water-based pigmented primer based on specially modified synthetic resins, for interior use. It can be used on metal, plastic, ceramic or properly prepared wood, to allow our finishes to be applied later.</p> <p>CEBOFIX EXTRA is available in 1 and 2,5 litres cans.</p>
Surface treatment of the substrate	<p>Untreated metal: degrease, brush and thoroughly clean the surface, on ferrous materials apply rust inhibitors before.</p> <p>Painted metal: degrease and clean the surface thoroughly, sandpapering and well remove dust.</p> <p>Plastic: degrease and clean the surface thoroughly, sandpapering and well remove dust.</p> <p>Untreated wood: prepare the surface with anti-tannin products to avoid yellowing.</p> <p>Painted wood: degrease and clean the surface thoroughly, sandpapering and well remove dust.</p> <p>Ceramic: degrease and thoroughly clean the surface.</p> <p>For kinds of substrates not included in this list, it is recommended to do a preliminary test before proceeding with the entire surface.</p>
Colouring	CEBOFIX EXTRA can't be coloured.
Application	Depending on the absorption of the substrate, CEBOFIX EXTRA can be applied in 1 or 2 layers, by brush or roller, diluted with 5-10% water. After complete drying (min. 24 hours) you can apply the choosed finish product.
VOC Classification (2004/42/CE Directive)	<p>Product category: Primers and fixatives (h)</p> <p>Maximum VOC content limit value (2010) for the ready-to-use product: 30 g/l.</p> <p>CEBOFIX EXTRA contains: 29 g/l VOC</p>
Technical characteristics	<p>Estimated Coverage: 8 – 10 m²/litre, for each layer.</p> <p>Appearance: liquid</p> <p>Density: 1.34 g/cm³</p> <p>pH: 8.5 – 9</p> <p>Drying time: 4-6 hours between the first and the second layer. Complete drying min. 24 hours, according to ambient temperature and relative humidity.</p>
Storage	Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.
Safety warnings	CEBOFIX EXTRA does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the related Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.