



## TECHNICAL DATA SHEET

TDS 03.003

### Product

### CEBORUSTIK

### Description

CEBORUSTIK is a decorative thick coating, based on aged lime putty with excellent properties of high permeability to water vapour and resistance to moulds and bacteria. It can be applied in a high or lower thicknesses, it has an excellent filling power and does not crack.

CEBORUSTIK, combined with CEBOFLOS colourable, natural wax, allows to obtain decorative rustic effects to reproduce the ancient plasters.

CEBORUSTIK is available in 5 kg and 20 kg containers.

### Surface treatment of the substrate

It can be applied over all substrates such as gypsum, lime or cement based fine render. Clean the surface then apply by roller a coat of CEBOFIX R, diluted with 20-30% water.

### Colouring

CEBORUSTIK shall not be coloured.

### Application

On the prepared surface apply CEBORUSTIK with a stainless steel trowel in a uniform layer; proceed with the decoration required with the same trowel or with the chosen tool (spatula, brush, etc.). It is also possible to re-pass the surface with the trowel while the product is withering, in order to smooth the parts in relief. Wait until the product is completely dry (minimum 24 hours).

**Interior application:** CEBORUSTIK, applied on interiors, is then protected with CEBOFLOS, colourable natural wax, to be applied with a synthetic sponge (or other tool) in a uniform layer all over the surface. Once the product is dry go over the surface with a soft cloth or glove to fix or to remove any excess product.

**Exterior application:** For the protection against atmospheric agents apply CEBO TECH, diluted 1:4 with water and in the required colour, in two coats with a synthetic sponge or glove.

**“Cracked” effect:** please consult the Technical Data Sheet of the product CEBOBREAK.

### Useful suggestions

Working and drying time is variable according to the ambient temperature and relative humidity as well as the thickness of product applied.

### VOC Classification (2004/42/CE Directive)

Product not intended for uses provided for by Dir. 2004/42/CE  
CEBORUSTIK contains: 20 g/l VOC

### Technical characteristics

Estimated Consumption: 0.6 – 1.8 kg/m<sup>2</sup> according to the method of application and the type of finish chosen

Appearance: dense paste

Specific weight: 1.66 g/cm<sup>3</sup>

pH: > 10

Resistance to washing: The product withstands ordinary cleaning maintenance.

Drying time: 4-6 hours between coats. Completely dry after minimum 24 hours, according to ambient temperature and relative humidity.

### Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

### Safety warnings

CEBORUSTIK is lime based and it is therefore highly alkaline. Use suitable eye protections. In case of contact with eyes, rinse immediately with plenty of water for at least 15 minutes; if irritations persist seek medical advice. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.