



TECHNICAL DATA SHEET

TDS 04.037

| | |
|--|--|
| Product | CEBOFREE BLACK |
| Description | <p>CeboFree is a multicolour water based finish for interiors, available in Black and White bases, easy to apply and highly versatile: when used in combination with CeboUp additive, permits to create polychromatic decorations with golden and silver metallic reflections.</p> <p>The combination of walls, decorated with CeboFree White, and walls or elements, decorated with CeboFree Black, allows to obtain modern and refined environments</p> |
| Packaging | CEBOFREE BLACK is available in 1 litres and 2,5 litres package. |
| Surface treatment of the substrate | <p>Verify that the surface is uniform, perfectly clean and dry.</p> <p>In case of recently repaired walls, highly absorbent or chalky substrates, carefully clean the surface and apply a coat of priming fixative CeboFix M, by paintbrush, diluted 1:1 with water.</p> <p>Then apply FondoPlus, water based, acrylic base coat with high covering properties and brilliant whiteness. Apply one or two coats of product, with a short hair woollen roller, until the surface is entirely covered.</p> <p>FONDOPLUS must be in the colour 254/2 for the successive application of CEBOFREE BLACK. Use FONDOPLUS in the white colour in the case of the following application of CEBOFREE WHITE.</p> |
| Colouring | CEBOFREE can be coloured with CEBOCOLORSTATION tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number. |
| Additives | CeboUp : special additive in paste form, based on luminiscent pigments. When added to CeboFree Black and White, gives the finish a precious metallic appearance. CeboUp is available in the following variety: 341 (silver) and 342 (gold). |
| Application | CEBOFREE is applied in one coat, with the appropriate Cebosi brush 2,5" (cod. A/26): dip the brush into the product and apply to the surface in crossed brush-strokes. After having applied 4-6 m ² , and in any case before the complete drying of the product, go over the painted surface with the special plastic spatula CARESS (A/38), pressing slightly. After the addition of colorants and additives, CeboFree Black must be used within 48 hours. |
| Useful suggestions | CEBOFREE can be applied over metal, wood, plastic; in this case it's necessary to prepare the surface with the appropriate primer. |
| VOC Classification (2004/42/CE Directive) | Product category: Decorative effect coating (I) Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l. CEBOFREE contains: 30 g/l VOC |
| Technical characteristics | Estimated coverage: 8 m ² /lt Appearance: dense liquid Specific weight: 1,03 g/cm ³ pH: 7 – 7,5 Resistance to washing: the product withstands ordinary cleaning maintenance. Drying time: 6-8 hours according to ambient temperature and relative humidity. |
| Storage | Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources. |
| Safety warnings | CEBOFREE does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with |



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Review n.2
Date: 21/10/2016

TECHNICAL DATA SHEET

TDS 04.037

eyes, rinse immediately with plenty of water; if irritations persist, seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.