



# TECHNICAL DATA SHEET

TDS 04.013

## Product

## CEBOVEL L

## Description

CEBOVEL L is a water based, acrylic, transparent, washable finish for interiors. Thanks to its combination with specific CeboVel Additives, it allows to create various decorations with pearly or iridescent effects.

CEBOVEL L is available in 900 ml and 4.5 litres containers.

## Surface treatment of the substrate

It is applied, suitably mixed with CeboVel Additive Cangiante or Perlato, on surfaces prepared with white or coloured CEBOTOP FONDO, to reach the desired decoration.

## Colouring

CEBOVEL L can be coloured with CeboColorStation tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

## Application

CEBOVEL L is ready-to-use and must be applied by paintbrush in vertical stripes of about one meter width and for the entire the height of the wall. Decorate the painted surface with a damp rag stippler, or different tool, to attain the required decoration. It is advised to leave an undecorated stripe of about 10 cm which will help avoiding joint marks.

## Useful suggestions

## VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)  
Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.  
CEBOVEL L contains: 35 g/l VOC

## Technical characteristics

Estimated Coverage: 4 - 5 m<sup>2</sup>/litre  
Appearance: liquid  
Specific weight: 1.03 g/cm<sup>3</sup>  
pH: 8 - 9  
Resistance to washing: The product withstands ordinary cleaning maintenance.  
Drying time: 4-6 hours according to ambient temperature and relative humidity.

## Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

## Safety warnings

CEBOVEL L does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.