



TECHNICAL DATA SHEET

TDS 04.016

Product

CEBOSTYLE

Description

CEBOSTYLE is a water based, washable, full hiding paint with a metallic finish, for interiors. It gives all surfaces a uniform colour with special reflections of light. It is available in ARGENTO (silver) and ORO (gold) bases.

CEBOSTYLE is available in 500 ml, 1 litre, 2.5 litres and 5 litres containers.

Surface treatment of the substrate

It can be applied over all substrates such as gypsum, lime or cement based fine render as long as properly treated. In case of rough substrates repair the surface with levelling paste.

Carefully clean the surface and, if necessary, repair and level the substrate. On new walls or in case of very absorbent walls, apply by brush a coat of pigmented acrylic fixative CEBOFIX PRIMO, diluted with 25-30% water.

Colouring

CEBOSTYLE can be coloured with CeboColorStation tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

Application

Apply CEBOSTYLE in two coats: the first one by roller and the second one by brush or glove according to the desired effect.

Apply the first coat of CEBOSTYLE, diluted with 10-15% water, with a short pile roller working in stripes of about 1 meter, from bottom to top, taking care in going over the applied product with the empty roller again.

When the first coat is completely dry (after about 4-6 hours), apply the second coat with the appropriate CeboSi brush (available in 2.5" and 4" size): apply on the surface with crossed brush-strokes avoiding clear-cut squaring.

The second coat can also be applied with woollen glove applying the non-diluted product in uniform, circular movements.

Useful suggestions

CEBOSTYLE can also be applied over metal, wood, glass or plastic. It is however important to treat the substrate with suitable primers.

VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)

Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.

CEBOSTYLE contains: 28 g/l VOC

Technical characteristics

Estimated Coverage: 10 – 12 m²/litre, in two coats, according to the method of application and type of finish chosen.

Appearance: liquid

Specific weight: 1.1 g/cm³

pH: 8.5 – 9

Resistance to washing: The product withstands ordinary cleaning maintenance.

Drying time: 4-6 hours according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOSTYLE does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.