



TECHNICAL DATA SHEET

TDS 04.018

Product

CEBOART PINTURA

Description

CEBOART PINTURA is a decorative paint for interiors and exteriors, based on seasoned, filtered lime putty that grants natural, high water vapour permeability, resistance to moulds and bacteria and long-lasting stability.

CEBOART PINTURA gives the surfaces a matt and softly shaded finish, typical of the old lime wash paints. It is therefore particularly indicated for the modern ecological building as well as for the historical restoration.

CEBOART PINTURA is available in 4 kg, 8 kg, 16 kg containers.

Surface treatment of the substrate

It can be applied to all substrates such as gypsum plaster, lime or cement based fine render. Carefully clean the surface and, if necessary, repair and level the substrate. Apply with a short pile roller or by brush one coat of CEBOFIX R, acrylic fixative, diluted with 20-30% water. In case of substrates which are highly irregular, it is advisable to apply one or more coats of CEBOFONDO, base coat, with a stainless steel trowel.

Colouring

CEBOART PINTURA can be coloured with CeboColorStation or with CeboKit universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

Application

Apply CEBOART PINTURA by brush, in two coats, diluted with 15-20% of water. Wait the complete drying of the product (4-6 hours) between coats.

Useful suggestions

It is recommended the application of a protective coat of CEBOFLOW, a transparent and water-repellent barrier which does not modify the aesthetic appearance and the water vapour permeability of CEBOART PINTURA. CEBOFLOW, which is also suitable for interiors, it has been specifically studied for outside protection against water and air pollution. Refer to the relative Technical Data Sheet for more details.

VOC Classification (2004/42/CE Directive)

Product not included in the annex
CEBOART PINTURA contains: 3 g/l VOC

Technical characteristics

Estimated Coverage: 6 – 7 m²/kg

Appearance: liquid

Specific weight: 1.4 g/cm³

pH: 11

Drying time: 4-6 hours between coats. Complete drying after at least 24 hours, according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOART PINTURA is a lime based product and it is therefore strongly alkaline. Use suitable eye protections. In case of contact wash with plenty of water for at least 15 minutes. If irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet implies the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.