



TECHNICAL DATA SHEET

TDS 04.028

Product

CEBOSPARK

Description

CEBOSPARK is a water based, matt paint for interiors to create a highly refined finish both for private houses and commercial areas. CEBOSPARK is easy to apply and it is therefore indicated for application on wide surfaces.

The product applied in one single coat gives a light and shade effect; a more uniform and full colour is attained with a two-coat application.

In both cases the addition of CEBOGLITTER enhances and embellish the surfaces alternating the matt appearance of the paint with the sparkling of the light reflected by the glitters. The system is highly versatile as it allows an infinite number of personal finishing according to the colour of the paint, the tone of the glitter and the type of application chosen.

CEBOSPARK, in both types, is available in 1 litre, 2.5 litres and 5 litres containers.

Surface treatment of the substrate

It can be applied over all substrates such as gypsum, lime or cement based fine render. Carefully clean the substrate. If necessary repair or level the surface, then apply one or two coats of FONDOPLUS by roller, diluted with 10% water.

Colouring

CEBOSPARK can be coloured with CeboColorStation tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

Application

Soft shaded effect: Colour CEBOSPARK, add the chosen CEBOGLITTER and dilute the product with 20% water. Use the appropriate CeboSi 2.5" or 4" brush and apply on the surface with crossed brush-strokes **in a single layer**.

Estimated coverage: 10 m²/litre

Full colour effect: Colour CEBOSPARK, add the chosen CEBOGLITTER and dilute the product with 20% water. Use the appropriate CeboSi 2.5" or 4" brush and apply on the surface with crossed brush-strokes **in two layers**. Wait the complete drying (6-8 hours) of the first layer before the application of the second.

CEBOGLITTER can be added to CEBOSPARK in both layers to reach a very sparkling and shining effect, or just in the second layer for a more subtle and refined finish.

Estimated coverage: 7 - 8 m²/litre

Useful suggestions

Add the CEBOGLITTER immediately prior to the application of the CEBOSPARK.

VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)

Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.

CEBOSPARK contains: 30 g/l VOC

Technical characteristics

Estimated Coverage: 7 - 10 m²/litre according to the type of finish required.

Appearance: liquid

Specific weight: 1.32 g/cm³

pH: 8.5 - 9

Resistance to washing: The product withstands ordinary cleaning maintenance.

Drying time: 6-8 hours according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOSPARK does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.