



TECHNICAL DATA SHEET

TDS 04.029

Product

CEBOSTONE METAL

Description

CEBOSTONE METAL is a water based, acrylic finish for interiors, ideal for application on all types of support. CeboStone Metal permits to easily create valuable decorations where the sandy effect is enhanced by the glamour of the metallic look and the alternating chiaroscuro effects and enchanting golden reflections. It is also possible to enrich the decoration with CEBOIRON GRIGIO, to attain a greater chromatic contrast.

CEBOSTONE METAL is available in 1 litre, 3 litres and 5 litres containers.

Surface treatment of the substrate

Carefully clean the substrate and apply one or two coats of FONDOPLUS with a short hair woollen roller, diluted with 10% water until the surface is entirely covered.

Colouring

CEBOSTONE METAL can be coloured with CeboColorStation tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

Application

Apply CeboStone Metal, diluted with maximum 10% water, in one coat, with a medium size paintbrush in crossed brush-strokes so as to obtain alternating smooth and rough areas.

When CeboStone Metal is perfectly dry, it is possible to give one coat of CEBOIRON GRIGIO, in the chosen colour; dip a synthetic sponge into the product and apply to the surface a uniform layer, avoiding build-up of material.

Useful suggestions

VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)
Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.
CEBOSTONE METAL contains: 40 g/l VOC

Technical characteristics

Estimated Coverage: 7 – 8 m²/litre according to the type of finish required.
Appearance: liquid
Specific weight: 1.46 g/cm³
pH: 8 – 9
Resistance to washing: The product withstands ordinary cleaning maintenance.
Drying time: 4-6 hours according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOSTONE METAL does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.