



TECHNICAL DATA SHEET

TDS 06.004

Product	CEBOFLOW
Description	<p>CEBOFLOW is a water based transparent protective product based on special newly developed fluoridated polymers. Ideal for interior application, it is however recommended on exterior due to its high resistance to rainwater and air pollution.</p> <p>CEBOFLOW is available in 1 litre and 2.5 litres containers.</p>
Surface treatment of the substrate	<p>CEBOFLOW, applied over CEBOART PINTURA, MARMORINO and POZZOLANO, form an invisible and water repellent barrier, without modifying the aesthetical aspect and the characteristics of water vapour permeability.</p> <p>It is also the ideal protection over CEBOSTONE on exterior application.</p>
Colouring	<p>CEBOFLOW shall not be coloured.</p>
Application	<p>CEBOFLOW is ready-to-use and it must be applied by brush in one coat to reach substrate saturation.</p>
Useful suggestions	<p>Apply the product from bottom to top to avoid dripping.</p>
VOC Classification (2004/42/CE Directive)	<p>Product category: Decorative effect coating (I) Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l. CEBOFLOW contains: 0.5 g/l VOC</p>
Technical characteristics	<p>Estimated Coverage: 10 m²/litre. Appearance: liquid Specific weight: 1.00 g/cm³ pH: 6 – 7 Resistance to washing: The product withstands ordinary cleaning maintenance. Drying time: 4-6 hours according to ambient temperature and relative humidity.</p>
Storage	<p>Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.</p>
Safety warnings	<p>CEBOFLOW does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately and show the safety data sheet of the product.</p>

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.