



TECHNICAL DATA SHEET

TDS 06.005

Product

CEBOTATTO

Description

CEBOTATTO is a transparent finish for interior decoration, based on organic fillers that create a gentle tactile sensation with a very matt visual effect. CEBOTATTO gives the surface excellent scratch resistance while enhancing the colour brightness.

CEBOTATTO is available in 1 litre and 4 litres containers.

Surface treatment of the substrate

CEBOTATTO is to be applied over CEBOSI SETOSO and CEBOTOP FONDO to emphasize the tactile effect of the finish.

Colouring

CEBOTATTO shall not be coloured.

Application

Apply CEBOTATTO over the perfectly dry CEBOSI SETOSO or CEBOTOP finish. Dilute CEBOTATTO maximum 5% with water and apply in one or two coats with a short-hair woollen roller, to reach the warm and comfortable sensation of the desired tactile effect.

Useful suggestions

VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)
Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.
CEBOTATTO contains: 40 g/l VOC

Technical characteristics

Estimated Coverage: 10 m²/litre.
Appearance: liquid
Specific weight: 1.00 g/cm³
pH: 8 – 9
Resistance to washing: The product withstands ordinary cleaning maintenance.
Drying time: 4-6 hours according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOTATTO does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately and show the safety data sheet of the product.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.