



Cebos Color Srl  
24040 Osio Sopra (BG)  
Via dei Dossi, 7  
Tel. +39 035 265141  
Fax +39 035 2651431  
C.F. & P.Iva 02567630161  
info@cebos.it  
www.ceboscolor.it

Review n.1  
Date: 19/02/2021

## TECHNICAL DATA SHEET

TDS. 027

### CeboMarmo

#### Description

**CeboMarmo:** precious water-based acrylic finish for interiors, with a glossy appearance. CeboMarmo reinterprets the marble effect by reproducing the movements of the typical veins and the brilliance of a precious and refined material, giving an exclusive charm to any environment.

#### Packages available

1,2 Lt – 4,8 Lt – 12 Lt

#### Coloring

The product can be coloured with CeboColorStation tinting system or with CEBOKIT universal colorants in the quantities indicated on the Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same batch number.

#### Dilution

Not required

#### Mixing:

Mix the product well before use.

#### Suitable surfaces:

All gypsum, lime and civil substrates are suitable. Check that the surfaces are perfectly clean, dry and uniform in appearance and absorption.

#### Preparation of the substrates:

Thanks to its characteristics of finesse and transparency, CeboMarmo allows to create extremely glossy marble effects; therefore, requires a careful evaluation of the support, which must be perfectly smooth and flat to the eye and to the touch; any imperfections must be previously eliminated. If during the application of CeboMarmo would be necessary to smooth the surface, it would be advisable to proceed respecting the direction and method of application of the chosen one.

In the presence of smoothing, chalking or absorbent substrates, first apply by brush a coat of CeboFix M transparent fixative diluted 1: 1 by volume with water.

#### Primer application

Before applying CeboMarmo it is necessary to prepare the surface with CeboFix Primo: white pigmented primer, for interiors, based on acrylic resins; suitable for application on gypsum, plasterboard or previously painted substrates. CeboFix Primo is applied in one or two coats, until the substrate is completely covered with a short-haired roller diluted 20% by volume with water.

#### Application

CeboMarmo is applied with a stainless steel trowel, in two or more coats depending on the chosen effect. Indications about the application are contained in the videos, application sheets, folders and catalogs.

#### Technical features:

Drying: 6-8 h

Theoretical yield: 4-5 sqm/lit

Physical aspect: white pasta

Specific weight: 1,78 g/cm<sup>3</sup>

pH: 9.1-9.5

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.



Cebos Color Srl  
24040 Osio Sopra (BG)  
Via dei Dossi, 7  
Tel. +39 035 265141  
Fax +39 035 2651431  
C.F. & P.Iva 02567630161  
info@cebos.it  
www.ceboscolor.it

Review n.1  
Date: 19/02/2021

## TECHINICAL DATA SHEET

TDS. 027

### **VOC classification (directive 2004/42 / EC):**

Product category: Paints for decorative effects (I)

Maximum allowable limit (2010) for ready-to-use product 200 g / l

CeboMarmo contains VOC: 96 g

### **Stockage**

The product has a guaranteed shelf life of 24 months if stored in original packaging at temperatures between +5 and +35 ° C, in a well-ventilated and dry place, away from sunlight and heat sources.

### **Safety indications:**

The product does not require particular environmental or personal protective measures; however it is advisable to avoid prolonged contact with the skin. In the event of eyes contact, immediately wash with clean water; if irritation occurs, consult a doctor. User information are contained in the relevant Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.