



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Cebos Color S.r.l.

Revision nr. 1

Dated 21/01/2020

First compilation

Printed on 21/05/2020

Page n. 1/13

S.S. 04.043 - CeboArt CalceFine

Safety Data Sheet

According to Annex II to REACH - Regulation 2015/830

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: **S.S. 04.043**
Product name: **CeboArt CalceFine**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **Wall coating based on slaked lime, for interiors and exteriors**

1.3. Details of the supplier of the safety data sheet

Name: **Cebos Color S.r.l.**
Full address: **Via Dei Dossi n. 7**
District and Country: **24040 OSIO SOPRA (BG)**
ITALY
Tel. (+39) 035 265141
Fax (+39) 035 2651431

e-mail address of the competent person
responsible for the Safety Data Sheet
Product distribution by:

carlo@cebos.it
Cebos Color S.r.l.

1.4. Emergency telephone number

For urgent inquiries refer to: **Contact your local poison information service.**
Technical information: Cebos Color Tel. (+39) 035 265141 (Lun-Ven 8.30/12.30 - 13.30/18.00)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2015/830. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Serious eye damage, category 1

H318

Causes serious eye damage.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

S.S. 04.043 - CeboArt CalceFine

Hazard pictograms:



Signal words: Danger

Hazard statements:

H318 Causes serious eye damage.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P280 Wear protective gloves / protective clothing / eye protection / face protection.
P302+P352 IF ON SKIN: wash with plenty of water / . . .
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P313 Get medical advice / attention.

Contains: CALCIUM HYDROXIDE

VOC (Directive 2004/42/EC) :

Decorative effect coatings.

VOC given in g/litre of product in a ready-to-use condition : 21,00
 Limit value: 200,00

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification 1272/2008 (CLP)
CALCIUM HYDROXIDE		
CAS 1305-62-0	$6 \leq x < 7$	Eye Dam. 1 H318, Skin Irrit. 2 H315, STOT SE 3 H335
EC 215-137-3		
INDEX -		
Reg. no. 01-2119475151-45-0174		
ETHANOLAMINE		
CAS 141-43-5	$0 \leq x < 0,05$	Acute Tox. 4 H302, Acute Tox. 4 H312, Acute Tox. 4 H332, Skin Corr. 1B



Cebos Color Srl
24040 Orio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651411
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Cebos Color S.r.l.

Revision nr. 1

Dated 21/01/2020

First compilation

Printed on 21/05/2020

Page n. 3/13

S.S. 04.043 - CeboArt CalceFine

H314, Eye Dam. 1 H318, STOT SE 3 H335

EC 205-483-3

INDEX 603-030-00-8

Reg. no. 01-2119486455-28

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures



Cebos Color Srl
28040 Ossio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651411
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Cebos Color S.r.l.

Revision nr. 1

Dated 21/01/2020

First compilation

Printed on 21/05/2020

Page n. 4/13

S.S. 04.043 - CeboArt CalceFine

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection

8.1. Control parameters

Regulatory References:

BGR	България	МИНИСТЕРСТВО НА ТРУДА И СОЦИАЛНАТА ПОЛИТИКА МИНИСТЕРСТВО НА ЗДРАВЕОПАЗВАНЕТО НАРЕДБА No 13 от 30 декември 2003 г (4 Септември 2018г)
DEU	Deutschland	TRGS 900 - Seite 1 von 69 (Fassung 29.03.2019)- Liste der Arbeitsplatzgrenzwerte und Kurzzeitwerte
ESP	España	LÍMITES DE EXPOSICIÓN PROFESIONAL PARA AGENTES QUÍMICOS EN ESPAÑA 2019 (INSST)
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en France. ED 984 - INRS
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Third edition,published 2018)
ITA	Italia	DIRETTIVA (UE) 2017/164 DELLA COMMISSIONE del 31 gennaio 2017
POL	Polska	ROZPORZADZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOLECZNEJ z dnia 12 czerwca 2018 r
PRT	Portugal	Ministério da Economia e do Emprego Consolida as prescrições mínimas em matéria de protecção dos trabalhadores contra os riscos para a segurança e a saúde devido à exposição a agentes químicos no trabalho - Diário da República, 1.ª série - N.º 111 - 11 de junho de 2018
ROU	România	HOTĂRÂRE nr. 584 din 2 august 2018 pentru modificarea Hotărârii Guvernului nr. 1.218/2006 privind



Cebos Color Srl
28040 Orio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 2651411
Fax +39 035 2651411
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Cebos Color S.r.l.

Revision nr. 1

Dated 21/01/2020

First compilation

Printed on 21/05/2020

Page n. 5/13

S.S. 04.043 - CeboArt CalceFine

EU
OEL EU
TLV-ACGIH

stabilirea cerințelor minime de securitate și sănătate în muncă pentru asigurarea protecției lucrătorilor împotriva riscurilor legate de prezența agenților chimici
Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 91/322/EEC.
ACGIH 2019

CALCIUM HYDROXIDE Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	1		4		RESP
AGW	DEU	1		2 (C)		INHAL
MAK	DEU	1		2		INHAL
VLA	ESP	1		4		
VLEP	FRA	5				
WEL	GBR	1		4		RESP
WEL	GBR	5				
VLEP	ITA	1	0	4	0	RESP
NDS/NDSch	POL	2		6		INHAL
NDS/NDSch	POL	1		4		RESP
VLE	PRT	1		4		RESP
TLV	ROU	1		4		RESP *13
OEL	EU	1		4		RESP
TLV-ACGIH		5				

ETHANOLAMINE Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	BGR	2,5	1	7,6	3	SKIN
AGW	DEU	0,5	0,2	0,5	0,2	SKIN
MAK	DEU	0,51	0,2	0,51	0,2	
VLA	ESP	2,5	1	7,5	3	SKIN
VLEP	FRA	2,5	1	7,6	3	SKIN
WEL	GBR	2,5	1	7,6	3	SKIN
VLEP	ITA	2,5	1	7,6	3	SKIN
NDS/NDSch	POL	2,5		7,5		SKIN
VLE	PRT	2,5	1	7,6	3	SKIN
TLV	ROU	2,5	1	7,6	3	SKIN
OEL	EU	2,5	1	7,6	3	SKIN
TLV-ACGIH		7,5	3	15	6	

Legend:



Cebos Color Srl
24040 Orio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651411
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Cebos Color S.r.l.

Revision nr. 1

Dated 21/01/2020

First compilation

Printed on 21/05/2020

Page n. 6/13

S.S. 04.043 - CeboArt CalceFine

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with category III work gloves (see standard EN 374).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	pasty
Colour	white
Odour	characteristic
Odour threshold	Not available
pH	> 10
Melting point / freezing point	Not available
Initial boiling point	Not available
Boiling range	Not available
Flash point	> 60 °C
Evaporation Rate	Not available



Cebos Color Srl
24040 Orio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651411
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Cebos Color S.r.l.

Revision nr. 1

Dated 21/01/2020

First compilation

Printed on 21/05/2020

Page n. 7/13

S.S. 04.043 - CeboArt CalceFine

Flammability of solids and gases	Not available
Lower inflammability limit	Not available
Upper inflammability limit	Not available
Lower explosive limit	Not available
Upper explosive limit	Not available
Vapour pressure	Not available
Vapour density	Not available
Relative density	1,8
Solubility	partially soluble in water
Partition coefficient: n-octanol/water	Not available
Auto-ignition temperature	Not available
Decomposition temperature	Not available
Viscosity	Not available
Explosive properties	Not available
Oxidising properties	Not available

9.2. Other information

VOC (Directive 2004/42/EC) :	2,00 % - 21,00 g/litre
VOC (volatile carbon) :	0,87 % - 8,70 g/litre

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

ETHANOLAMINE

May react dangerously with: acrylonitrile, chloroepoxypropane, chlorosulphuric acid, hydrogen chloride, iron-sulphur compounds, acetic acid, acetic anhydride, mesityl oxide, nitric acid, sulphuric acid, strong acids, vinyl acetate, cellulose nitrate.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

ETHANOLAMINE

Avoid exposure to: air, sources of heat.



Cebos Color Srl
28040 Oleggio (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651411
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Cebos Color S.r.l.

Revision nr. 1

Dated 21/01/2020

First compilation

Printed on 21/05/2020

Page n. 8/13

S.S. 04.043 - CeboArt CalceFine

10.5. Incompatible materials

ETHANOLAMINE

Incompatible with: iron, strong acids, strong oxidants.

10.6. Hazardous decomposition products

ETHANOLAMINE

May develop: nitric oxide, carbon oxides.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

LC50 (Inhalation) of the mixture:

Not classified (no significant component)

LD50 (Oral) of the mixture:

Not classified (no significant component)

LD50 (Dermal) of the mixture:

Not classified (no significant component)

CALCIUM HYDROXIDE

LD50 (Oral) 7340 mg/kg Rat



Cebos Color Srl
24040 Orio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651411
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Cebos Color S.r.l.

Revision nr. 1

Dated 21/01/2020

First compilation

Printed on 21/05/2020

Page n. 9/13

S.S. 04.043 - CeboArt CalceFine

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye damage

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

Information not available

12.2. Persistence and degradability

ETHANOLAMINE



Cebos Color Srl
24040 Orio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Cebos Color S.r.l.

Revision nr. 1

Dated 21/01/2020

First compilation

Printed on 21/05/2020

Page n. 10/13

S.S. 04.043 - CeboArt CalceFine

Solubility in water 1000 - 10000 mg/l

Rapidly degradable

CALCIUM HYDROXIDE

Solubility in water 1000 - 10000 mg/l

12.3. Bioaccumulative potential

ETHANOLAMINE

Partition coefficient: n-octanol/water -2,3

12.4. Mobility in soil

ETHANOLAMINE

Partition coefficient: soil/water -0,5646

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

12.6. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number

Not applicable

14.2. UN proper shipping name



Cebos Color Srl
24040 Orio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651411
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Cebos Color S.r.l.

Revision nr. 1

Dated 21/01/2020

First compilation

Printed on 21/05/2020

Page n. 11/13

S.S. 04.043 - CeboArt CalceFine

Not applicable

14.3. Transport hazard class(es)

Not applicable

14.4. Packing group

Not applicable

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EC: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage greater than 0,1%.



Cebos Color Srl
24040 Orio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651411
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Cebos Color S.r.l.

Revision nr. 1

Dated 21/01/2020

First compilation

Printed on 21/05/2020

Page n. 12/13

S.S. 04.043 - CeboArt CalceFine

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

VOC (Directive 2004/42/EC) :

Decorative effect coatings.

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.


SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Acute Tox. 4	Acute toxicity, category 4
Skin Corr. 1B	Skin corrosion, category 1B
Eye Dam. 1	Serious eye damage, category 1
Skin Irrit. 2	Skin irritation, category 2
STOT SE 3	Specific target organ toxicity - single exposure, category 3
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H315	Causes skin irritation.
H335	May cause respiratory irritation.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAS NUMBER: Chemical Abstract Service Number

 <p> Cebos Color Srl 24040 Orio Sopra (BG) Via dei Dossi, 7 Tel. +39 035 265141 Fax +39 035 2651411 C.F. & P.Iva 02567630161 info@cebos.it www.ceboscolor.it </p>	<div> Cebos Color S.r.l. </div> <div> S.S. 04.043 - CeboArt CalceFine </div>	Revision nr. 1 Dated 21/01/2020 First compilation Printed on 21/05/2020 Page n. 13/13
--	--	---

- CE50: Effective concentration (required to induce a 50% effect)
- CE NUMBER: Identifier in ESIS (European archive of existing substances)
- CLP: EC Regulation 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX NUMBER: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: EC Regulation 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
 3. Regulation (EU) 790/2009 (I Atp. CLP) of the European Parliament
 4. Regulation (EU) 2015/830 of the European Parliament
 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
 10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
 13. Regulation (EU) 2017/776 (X Atp. CLP)
 14. Regulation (EU) 2018/669 (XI Atp. CLP)
 15. Regulation (EU) 2018/1480 (XIII Atp. CLP)
 16. Regulation (EU) 2019/521 (XII Atp. CLP)
- The Merck Index. - 10th Edition
 - Handling Chemical Safety
 - INRS - Fiche Toxicologique (toxicological sheet)
 - Patty - Industrial Hygiene and Toxicology
 - N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
 - IFA GESTIS website
 - ECHA website
 - Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

Product's classification is based on the calculation methods set out in Annex I of the CLP Regulation, unless otherwise indicated in sections 11 and 12.

The data for evaluation of chemical-physical properties are reported in section 9.