



## TECHNICAL DATA SHEET

TDS 04.034

### Product

### CEBOGRANIT

### Description

CEBOGRANIT is a breathable decorative coating for interiors and exteriors, based on acrylic resins and natural sand, coated with weatherproof and sunlight resistant pigments. It allows to achieve mat and uniform surfaces with a delicate dotted effect. Its opacity, high mechanical strength, the low dirt pickup, make CEBOGRANIT the ideal solution for the decoration of private houses, public places (shops, offices, hotels, staircases and entrances) and prestigious wall facades.

CEBOGRANIT is available in 3 litres and 15 litres containers.

### Surface treatment of the substrate

It can be applied on all substrates such as gypsum, lime or cement based fine render. After the cleaning and the final preparation of the surface, apply by roller or brush a coat of the pigmented breathable fixative CEBOFIX R, diluted on 20-30% with water.

### Colouring

CEBOGRANIT can be coloured with CEBOCOLORSTATION tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

### Application

CEBOGRANIT is ready-to-use and must be applied in two coats with a stainless steel trowel. Apply the first coat of the product, smoothing perfectly the surface to remove any imperfections and attain a uniform layer. When the first coat is completely dry (minimum 12 hours), apply the second coat in the same way. Before the surface is completely dry, smooth the surface with the trowel in order to compact product.

### Useful suggestions

When CEBOGRANIT is completely dry (minimum 24 hours) apply CEBOFLOW, suitable for interiors and exteriors, in order to protect the surface from dirty water, leaving the original appearance of the product.  
For more information, consult the relevant Technical Data Sheet.

### VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)  
Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.  
CEBOGRANIT contains: 30 g/l VOC

### Technical characteristics

Estimated Coverage: 1,2 – 1,4 m<sup>2</sup>/litre  
Appearance: dense paste  
Specific weight: 1.75 g/cm<sup>3</sup>  
pH: 8,5 – 9  
Resistance to washing: The product withstands ordinary cleaning maintenance.  
Drying time: 24 hours according to ambient temperature and relative humidity.

### Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

### Safety warnings

CEBOGRANIT does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.