



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Review n.1
Date: 05/11/2019

TECHNICAL DATA SHEET

TDS I.007

CeboSil

Description

Water-based, transparent, matt, acrylic-siloxane resin-based finish for interiors and exteriors.

Packaging available

1 Lt – 2,5 Lt

Coloration

The product can be colored with the CeboColorStation tinting system or with the CeboKit universal dyes in the dosages indicated on the color cards. Obviously, different colors than those shown in the chart are possible to obtain varying the dosages provided and / or mixing the dyes together. Having to prepare several packs of the same color it is advisable to use dyes and products of the same production batch.

Dilution

0 to 1:1 by volume with water.

Mixing

Mix the product well before the usage.

Suitable surfaces

All plaster, lime and civil substrates are suitable. The substrates have to be perfectly clean, dry and uniform in appearance and absorption.

Surfaces preparation

CeboSil is a protective finish, it can be applied on different products of the Cebos Color line; for the right preparation of the support, refer to the technical data sheet of the product used for the realization of the chosen effect.

Application

CeboSil can be applied on completely dry surfaces, neutral or colored, suitably diluted, in one hand, with a synthetic sponge or brush, following the direction of the previously created design; proceed with the application from bottom to up to avoid dripping.

The informations on the application are contained in the videos, folders and catalogs available on: www.ceboscolor.it

Technical features

Drying: 4-6 h

Theoretical yield: 10 m² / L of diluted product.

Physical aspect: liquid, transparent.

Specific Weight: 1.02 g / cm³

pH: 8.5-9

VOC classification (directive 2004/42 / CE)

Product Category: Paints for decorative effects (I)

Maximum allowed limit (2010) for ready-to-use product 200 g / l

CeboSil contains VOC: 10g / l

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Review n.1
Date: 05/11/2019

TECHNICAL DATA SHEET

TDS I.007

Storage

The product has a guaranteed duration of 24 months if stored in original packaging at temperatures between +5 and +35 ° C, in a well-dry and well-ventilated place, away from sunlight and sources of heat.

Safety indications

The product does not require special environmental or personal protective measures; however it is advisable to avoid prolonged contact with the skin. In case of contact with eyes, immediately wash them with clean water; if irritation occurs, consult a doctor. The information for the user is contained in the relevant Safety Data Sheet available on: www.ceboscolor.it

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.

Cebos Color Srl - sistemi decorativi murali - codice fiscale/partita iva 02567630161