



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Review n.1
Date: 01/03/2011

TECHNICAL DATA SHEET

TDS 01.001

Product

CEBOFONDO

Description

CEBOFONDO is universal rendering based on slake lime and marble powders, with a slightly porous effect, for levelling interior and exterior surfaces also when a thick coating is needed. Due to its highly breathing characteristics it is the ideal base coat on irregular surfaces which are to be decorated with a lime based finish of the CeboArt line.

CEBOFONDO is available in 5 kg and 20 kg containers.

Surface treatment of the substrate

It can be applied over substrates based on gypsum, lime or cement fine rendered mortar or previously painted. On the properly restored surface, free from dust and foreign substances, apply by paint brush or roller a coat of CEBOFIX R diluted 20-30% with water.

Colouring

CEBOFONDO shall not be coloured.

Application

CEBOFONDO is ready to use and must be applied with a stainless steel trowel in one or more coats according to the thickness required. Before the product is completely dry, smoothen and compact the surface, always with the stainless steel trowel.

Useful suggestions

It is possible to wet the trowel or the support, before the final smoothing to eliminate all imperfections or the marks of the trowel.

VOC Classification (2004/42/CE Directive)

Product category: Product not included in the annex.
CEBOFONDO contains: 21 g/l VOC

Technical characteristics

Estimated Coverage: 1.2-1.5 kg/m²
Appearance: dense paste
Specific weight: 1.83 g/cm³
pH: >10
Drying time: minimum 24 hours according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOFONDO is a lime based product and it is therefore strongly alkaline. Use suitable eye protections. In case of contact wash with plenty of water for at least 15 minutes. If irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.