

TECHNICAL DATA SHEET TDS 01.003

Product CEBOFIX PRIMO

Description CEBOFIX PRIMO is a white, water based, acrylic fixative.

It is used for substrate preparation for interiors.

The white appearance and the specific formulation allow CEBOFIX PRIMO to uniform the absorption of the substrate, improve the application, the coverage and the chromatic harmony of the following coats of Cebos finishes.

It is especially recommended in case of substrates which are absorbent, non-homogeneous or repaired with levelling paste.

CEBOFIX PRIMO is available in 1 litre, 5 litres, 10 litres containers.

Surface treatment of the substrate

It can be applied over substrates based on gypsum, lime or cement fine rendered mortar, properly restored and free from dust and foreign substances.

Colouring CEBOFIX PRIMO shall not be coloured.

Application CEBOFIX PRIMO can be applied by brush, diluted with 25-30% water, in one or more

coats according to the absorption of the substrate.

Wait until the product is completely dry (minimum 24 hours) before the application of the

chosen Cebos finish.

Useful suggestions

VOC Classification (2004/42/CE Directive)

Product category: Binding primers (h).

Maximum VOC content limit value (2010) for the ready-to-use product: 30 g/l.

CEBOFIX PRIMO contains: 12 g/l VOC

Technical characteristics Estimated Coverage: 10-12 m²/litre per coat.

Appearance: liquid

Specific weight: 1.36 g/cm³

pH: 8.5 - 9

Drying time: 4-6 hours between coats; complete drying after at least 24 hours according

to ambient temperature and relative humidity.

Storage Storage Store the product in its original containers, tightly closed at ambient temperature

between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct

sunshine and heat sources.

Safety warnings CEBOFIX PRIMO does not require any specific personal or environmental protection

measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately and show the safety data sheet of the

product.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.