



Cebos Color Srl  
24040 Osio Sopra (BG)  
Via dei Dossi, 7  
Tel. +39 035 265141  
Fax +39 035 2651431  
C.F. & P.Iva 02567630161  
info@cebos.it  
www.ceboscolor.it

Review n.1  
Date: 01/03/2011

## TECHNICAL DATA SHEET

TDS 02.002

### Product

### CEBOSI FONDO

### Description

CEBOSI FONDO is an acrylic water based washable paint, with a slightly rough texture, for interiors and exteriors.  
It is used as coloured base coat prior to the application of decorative paints CEBOSI RIFLESSI, CEBOSI UNIVERSAL, CEBOSI DECORO.

CEBOSI FONDO is available in 1 litre, 2.5 litres, 5 litres and 10 litres containers.

### Surface treatment of the substrate

It can be applied over substrates based on gypsum, lime or cement fine rendered mortar, properly restored and free from dust and foreign substances.

### Colouring

CEBOSI FONDO can be coloured with CeboColorStation tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

### Application

CEBOSI FONDO has to be applied by short pile roller in one or two coats to reach a perfect coverage of the substrate; in case of substrates which are highly absorbent, give a first coat of CEBOSI FONDO diluted 30% with water.

### Useful suggestions

### VOC Classification (2004/42/CE Directive)

Product category: Interior matt walls and ceilings (a).  
Maximum VOC content limit value (2010) for the ready-to-use product: 30 g/l.  
CEBOSI FONDO contains: 15 g/l VOC

### Technical characteristics

Estimated Coverage: 10 m<sup>2</sup>/litre per coat.  
Appearance: liquid  
Specific weight: 1.47 g/cm<sup>3</sup>  
pH: 8.5 – 9  
Drying time: 6-8 hours, according to ambient temperature and relative humidity.

### Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

### Safety warnings

CEBOSI FONDO does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately and show the safety data sheet of the product.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.