



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Revisione n.1
Data revisione: 01/03/2011

TECHNICAL DATA SHEET

TDS 03.001

Product	CEBOBREAK
Description	<p>CEBOBREAK is a gloss, transparent, intermediate coat based on acrylic resins. It has been studied to attain the "Cracked" effect for interiors.</p> <p>CEBOBREAK is available in 1 lt containers.</p>
Surface treatment of the substrate	<p>It can be applied over substrates based on gypsum, lime or cement fine rendered mortar, properly restored and free from dust and foreign substances.</p> <p>Apply by roller or brush the coloured CEBOFIX R, diluted with 20-30% water, in one or more coats according the absorption of the substrate.</p>
Colouring	<p>CEBOBREAK shall not be coloured.</p>
Application	<p>CEBOBREAK is ready-to-use. Apply by brush in one coat until the surface is completely soaked.</p> <p>After a minimum of 4 hours and within 24 hours maximum, apply one coat of CeboRustik. When CeboRustik is complete dry (minimum 24 hours) apply CeboFlos. Refer to CeboRustik colour guide for the colouring instructions of CeboFix R and CeboFlos and for the description of the complete application cycle.</p>
Useful suggestions	<p>Apply the product from bottom to top to avoid marks due to dripping of the product on the surface.</p>
VOC Classification (2004/42/CE Directive)	<p>Product category: Binding primers (h). Maximum VOC content limit value (2010) for the ready-to-use product: 30 g/l. CEBOBREAK contains: 10 g/l VOC</p>
Technical characteristics	<p>Estimated Coverage: 10-12 m²/litre per coat. Appearance: liquid Specific weight: 1.07 g/cm³ pH: 4.5 – 5</p> <p>Drying time: 4-6 hours according to ambient temperature and relative humidity.</p>
Storage	<p>Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.</p>
Safety warnings	<p>CEBOBREAK does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately and show the safety data sheet of the product.</p>

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.