



TECHNICAL DATA SHEET

TDS 04.004

Product CEBOKISS

Description CEBOKISS is transparent finish for interiors based on special multi-coloured flecks

which create a special visual effect. CEBOKISS also improves colour brightness.

CEBOKISS is available in 1 litre and 2.5 litres containers.

Surface treatment of the

substrate

CEBOKISS must be applied over perfectly dry surfaces painted with CEBOSTONE.

It can also be used on all Cebos acrylic decorative paints.

Colouring CEBOKISS shall not be coloured.

Application CEBOKISS must be applied in one coat with crossed brush-strokes.

In case of application on smooth surfaces or on dark colours, dilute the product with 10-

15% of water.

CEBOKISS cannot be applied over lime based products.

Useful suggestions In case of use over other acrylic decorative paints, it is advisable to carry out a

preventive test before application.

VOC Classification Product category: Decorative effect coating (I)

(2004/42/CE Directive) Maximum VOC content limit value (2010) for the ready-to-use product: 200 q/l.

CEBOKISS contains: 36 g/l VOC

Technical characteristics Estimated Coverage: 10 m²/litre

Appearance: liquid

Specific weight: 1.04 g/cm³

pH: 8.5 - 9

Resistance to washing: The product withstands ordinary cleaning maintenance. Drying time: 4-6 hours according to ambient temperature and relative humidity.

Storage Store the product in its original containers, tightly closed at ambient temperature

between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct

sunshine and heat sources.

Safety warnings CEBOKISS does not require any specific personal or environmental protection

measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the

relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.