



# TECHNICAL DATA SHEET

**TDS 04.009**

## Product

## CEBOTREND

## Description

CEBOTREND is a water based, decorative finish for interiors. It is suitable for all areas, it is easy to apply and fairly washable. It allows to create various effects which range from soft shades of light colours to the special contrasts and speckles of dark colours. CEBOTREND can also be combined with CEBOSTYLE ANTICO to create charming surfaces where the metallic and multi-coloured effects meet. CEBOTREND can also be enriched with the addition of CEBOLUX precious additive based on natural mica which adds to the finish deep touches of light.

CEBOTREND is available in 1 litre, 3 litres and 5 litres containers.

## Surface treatment of the substrate

It can be applied over all substrates such as gypsum, lime or cement based fine render. Carefully clean the substrate. If necessary repair or level the surface, then apply one or two coats of FONDOPLUS with a short hair woollen roller, until the surface is entirely covered. FONDOPLUS can be used both in white or coloured according to the final chromatic effect desired.

## Colouring

CEBOTREND can be coloured with CeboColorStation tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

## Application

Apply CEBOTREND with a synthetic glove in circular, light and uniform movements. After having applied 1-2 m<sup>2</sup> go over the surface again with the empty glove to even the quantity of material. The product must be used within 6 days after colouring and/or mixing with additives. Refer to the specific Colour card to choose the required combination with CEBOSTYLE ANTICO bases.

## Useful suggestions

## VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)  
Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.  
CEBOTREND contains: 15 g/l VOC

## Technical characteristics

Estimated Coverage: 5-6 m<sup>2</sup>/litre  
Appearance: dense liquid  
Specific weight: 1.03 g/cm<sup>3</sup>  
pH: 7 – 7.5  
Resistance to washing: The product withstands ordinary cleaning maintenance.  
Drying time: 6-8 hours according to ambient temperature and relative humidity.

## Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

## Safety warnings

CEBOTREND does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.