



TECHNICAL DATA SHEET

TDS 04.017

Product

CEBOSTYLE ANTICO

Description

CEBOSTYLE ANTICO is a water based, washable, full hiding paint with a metallic finish. It gives all surfaces special light contrasts which enhance all classic or modern rooms as requested by the latest trends in interior design.
It is available in 13 ready-to-use bases.

CEBOSTYLE ANTICO is available in 500 ml, 1 litre, 2.5, 5 litres containers.

Surface treatment of the substrate

It can be applied over all substrates such as gypsum, lime or cement based fine render as long as properly treated.

Application by brush or “crepé” effect: Carefully clean the surface and, if necessary, repair and level the substrate. Apply with a short-hair woollen roller one or two coats of FONDOPLUS, acrylic base coat for interiors, diluted 10% with water.

BARKODE effect: see CEBOIDEA Technical Data Sheet

DRAFT and FUSION effect: see CEBOSTRONG Technical Data Sheet

Colouring

CEBOSTYLE ANTICO can be coloured with CeboColorStation tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

Application

Application by brush: Apply CEBOSTYLE ANTICO in two coats, without dilution, with the appropriate CeboSi brush (available in 2.5” and 4” size): dip the brush into the product and apply on the surface in crossed brush-strokes avoiding clear-cut squaring. When the first coat is completely dry (after about 4-6 hours), apply the second coat with the same technique.

“Crepé” effect: On a smooth surface apply CEBOSTYLE ANTICO in two coats, without dilution, with a short-hair woollen roller in a uniform layer on the full height of the wall, taking care in going over the applied product with the empty roller again.

After about 4-6 hours apply CEBOSTYLE ANTICO by brush in a uniform layer, in vertical stripes of about 1 metre on the entire wall; decorate the product just applied with the special rag-stippling trowel, or any other tool; it is advisable to leave a 10 cm undecorated stripe as connection with the following application step.

Application of CEBOSTYLE ANTICO over CEBOSTONE: On the properly treated substrate apply CEBOSTONE white, diluted maximum 5% with water, with a medium size paintbrush in crossed directions. When CEBOSTONE is completely dry (after about 6-8 hours), apply CEBOSTYLE ANTICO without dilution, in two coats with a brush or synthetic glove; dip the tool into the product and apply on the surface in avoiding clear-cut squaring. When the first coat is completely dry (after about 4-6 hours), apply the second coat with the same technique.

BARKODE Effect: Over the dry coat of CEBOIDEA apply CEBOSTYLE ANTICO in two coats, with the appropriate CeboSi brush, following the direction of the decoration previously done. The first coat must be dry before the application of second coat. Refer to the relative Colour Card to choose the colour combination and for full description of the application cycle.

FUSION and DRAFT Effect: Over the dry coat of CEBOSTRONG apply CEBOSTYLE ANTICO in two coats, with the appropriate CeboSi brush, following the direction of the decoration previously done. The first coat must be dry before the application of second coat. Refer to the relative Colour Card to choose the colour combination and for full description of the application cycle.



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Review n.1
Date: 01/03/2011

TECHNICAL DATA SHEET

TDS 04.017

Useful suggestions

CEBOSTYLE ANTICO can be also be applied over metal, wood, glass or plastic. It is however important to treat the substrate with suitable primers.

VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)
Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.
CEBOSTYLE ANTICO contains: 31 g/l VOC

Technical characteristics

Estimated Coverage: 6 – 12 m²/litre, in two coats, according to the method of application and type of finish chosen.
Appearance: liquid
Specific weight: 1.1 g/cm³
pH: 8.5 – 9
Resistance to washing: The product withstands ordinary cleaning maintenance.
Drying time: 4-6 hours according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOSTYLE ANTICO does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.