



TECHNICAL DATA SHEET

TDS 04.020

Product

CEBOART MARMORINO

Description

CEBOART MARMORINO is a decorative plaster for interiors and exteriors, based on seasoned, filtered lime putty that grants a natural and perfect adhesion to the substrates, high water vapour permeability, resistance to moulds and bacteria and long-lasting stability.

CEBOART MARMORINO is the ideal product to recreate stylish satin finishes with a delicate dotted effect, as the classical marmorino finish.

CEBOART MARMORINO is available in 5 kg and 20 kg containers.

Surface treatment of the substrate

It can be applied over all substrates such as gypsum plaster, lime or cement based fine render. Carefully clean the surface and, if necessary, repair and level the substrate. Apply with a short pile roller or by brush one coat of CEBOFIX R, pigmented, acrylic fixative, diluted 20-30% with water.

Colouring

CEBOART MARMORINO can be coloured with CeboColorStation or with CeboKit universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

Application

CEBOART MARMORINO is ready to use and must be applied in two coats with a stainless steel trowel. Apply a first layer of product in a uniform thickness. When the first coat is completely dry, apply the second coat being careful to compact very well the product.

Useful suggestions

When CEBOART MARMORINO is thoroughly dry (minimum 24 hours), to protect the finish from dirt and water, apply a coat of CEBOFLOW, for interiors and exteriors. To increase the natural satin effect the plaster and to give water repellence to the surface, when CEBOART MARMORINO is thoroughly dry (minimum 24 hours) apply a coat of ECOCERA, only for interiors.

Refer to the relative Technical Data Sheets for more details.

VOC Classification (2004/42/CE Directive)

Product not included in the annex
CEBOART MARMORINO contains: 21 g/l VOC

Technical characteristics

Estimated Coverage: 1 m²/kg
Appearance: dense paste
Specific weight: 1.75 g/cm³
pH: >10
Drying time: minimum 24 hours according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOART MARMORINO is a lime based product and it is therefore strongly alkaline. Use suitable eye protections. In case of contact wash with plenty of water for at least 15 minutes. If irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.