

TECHNICAL DATA SHEET TDS 04.025

Product

CEBOIRON GRIGIO & NERO

Description

CEBOIRON type GRIGIO (Grey) and NERO (Black) is a water based semi-hiding finish for interiors, with micaceous and pearly pigments.

CEBOIRON is available in 1 litre and 2.5 litres containers.

Surface treatment of the substrate

CEBOIRON must be applied on surfaces which have been painted with CEBOSTYLE ANTICO and previously decorated with CEBOIDEA and CEBOSTRONG.

BARKODE effect: see CEBOIDEA Technical Data Sheet

DRAFT and FUSION effect: see CEBOSTRONG Technical Data Sheet

Colouring

CEBOIRON type GRIGIO and NERO shall not be coloured.

Application

BARKODE Effect: Over the dry coat of CEBOIDEA and CEBOSTYLE ANTICO, apply one coat of CEBOIRON by stainless steel trowel following the direction of the previously done decoration and taking care to remove with the trowel itself, the excess material so as to enhance the areas in relief.

Refer to the relative Colour Card to choose the colour combination and for full description of the application cycle.

FUSION and DRAFT Effect: Over the dry coat of CEBOSTRONG and CEBOSTYLE ANTICO, apply one coat of CEBOIRON by stainless steel trowel following the direction of the previously done decoration and taking care to remove with the trowel itself, the excess material so as to enhance the areas in relief.

Refer to the relative Colour Card to choose the colour combination and for full description of the application cycle.

Useful suggestions

VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)

Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.

CEBOIRON contains: 30 g/l VOC

Technical characteristics

Estimated Coverage: 15 - 18 m²/litre

Appearance: dense liquid

Specific weight: 1.1 g/cm³ (Grey) – 1.23 g/cm³ (Black)

pH: 8.5 – 9

Resistance to washing: The product withstands ordinary cleaning maintenance. Drying time: 4-6 hours according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOIRON does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.