



TECHNICAL DATA SHEET

TDS 04.033

Product

CEBOTOP PAINT

Description

CEBOTOP PAINT is an high quality, acrylic water based paint for interiors, with a smooth and matt finish. In addition to its characteristics of high covering and resistance to washing, CeboTop Paint has excellent properties of colour development to obtain matt and masking colours even in the deepest tones.

The matching shades of the TeamCard colour collection, makes CeboTop Paint the ideal complement to emphasize and outline all decorative effects created with the wide range of Cebos Color finishes.

CEBOTOP PAINT BIANCO (White) is available in 1 litre, 5 litres and 10 litres containers.
CEBOTOP PAINT BASE is available in 1 litre, 2.5 litres and 5 litres containers.

Surface treatment of the substrate

It can be applied over substrates based on gypsum, lime or cement fine rendered mortar or previously painted, properly restored and free from dust and foreign substances. In case of particularly absorbent or chalky substrates, apply a coat of CEBOFIX M diluted 1:1 with water, by brush.

Colouring

CEBOTOP PAINT can be coloured with CeboColorStation tinting system or with CEBOKIT universal colorants in the quantities indicated on our Colour Cards. It is also possible to create different shades in addition to those presented on our Colour Cards by varying the quantities or by mixing different colorants. If more than one pack has to be produced in the same colour, it is advisable to use bases and colorants carrying the same lot number.

Application

CEBOTOP PAINT must be applied by brush or roller in two coats, diluted 20% with water. Wait 4-6 hours between the first and the second coat.

Useful suggestions

VOC Classification (2004/42/CE Directive)

Product category: Interior matt walls and ceilings (a).
Maximum VOC content limit value (2010) for the ready-to-use product: 30 g/l.
CEBOTOP PAINT contains: 20 g/l VOC

Technical characteristics

Estimated Coverage: 7 m²/litre per coat.
Appearance: liquid
Specific weight: BIANCO 1.56 g/cm³ - BASE 1.47 g/cm³
pH: 8 – 9
Drying time: 4-6 hours, according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOTOP PAINT does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately and show the safety data sheet of the product.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.