



SCHEDA TECNICA

ST 04.034

Product

CEBOGRANIT

Description

CEBOGRANIT decorative, breathable wall coating for interiors and exteriors, based on acrylic resin and natural sands coated with weatherproof and sunlight resistant pigments. It allows to achieve mat and uniform surfaces with a delicate dotted effect. Its opacity, its high strength and its low dirt pick-up make CeboGranit the ideal solution to embellish private houses, public places (shops, office, hotels, halls, staircases) and prestigious wall façades.

CEBOGRANIT is available in 3 Lt. and 15 Lt.

Surface treatment of the substrate

It can be applied over all substrates such as gypsum, lime or cement based fine render. Clean the surface then apply by roller or brush a coat of CEBOFIX R, diluted with 20-30% water.

Colouring

CEBOGRANIT can be coloured with CeboColorStation or with CeboKit universal colorants in the quantities indicated on our Colour Cards. If more than one pack has to be produced in the same colour; it is advisable to use bases and colorants carrying the same lot number.

Application

CEBOGRANIT is ready to use and must be applied in two coats with a stainless steel trowel. Apply a first layer of product in a uniform thickness. When the first coat is completely dry (min. 12 hours), apply the second coat being careful to compact very well the product. Before completely dry, retouch the surface with clean trowel for compacting layer.

Useful suggestions

When CEBOGRANIT is thoroughly dry (minimum 24 hours), to protect the finish from dirt and water, apply a coat of CEBOFLOW, for interiors and exteriors.

VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)
Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.
CEBOGRANIT contains: 40 g/l VOC

Technical characteristics

Estimated Coverage: 1,2-1,4 m²/Lt.
Appearance: dense paste
Specific weight: 1.75 g/cm³
pH: 8,5-9
Drying time: minimum 24 hours according to ambient temperature and relative humidity.
Resistance to washing: The product withstands ordinary cleaning maintenance.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources

Safety warnings

CEBOGRANIT does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately. The users' information is contained in the relative Safety Data Sheet

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.