



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Review n.1
Date: 01/03/2011

TECHNICAL DATA SHEET

TDS 06.004

Product

CEBOFLOW

Description

CEBOFLOW is a water based transparent protective product based on special newly developed fluoridated polymers. Ideal for interior application, it is however recommended on exterior due to its high resistance to rainwater and air pollution.

CEBOFLOW is available in 1 litre and 2.5 litres containers.

Surface treatment of the substrate

CEBOFLOW, when applied on CEBOART PINTURA, MARMORINO and POZZOLANO, forms an invisible and water repellent barrier, without modifying the aesthetical aspect and the characteristics of water vapour permeability of the finish. It is also the ideal protection over CEBOSTONE on exterior application.

Colouring

CEBOFLOW shall not be coloured.

Application

CEBOFLOW is ready-to-use and it must be applied by paintbrush in one coat to reach the substrate saturation.

Useful suggestions

Apply the product from bottom to top to avoid dripping.

VOC Classification (2004/42/CE Directive)

Product category: Decorative effect coating (I)
Maximum VOC content limit value (2010) for the ready-to-use product: 200 g/l.
CEBOFLOW contains: 0.5 g/l VOC

Technical characteristics

Estimated Coverage: 10 m²/litre.
Appearance: liquid
Specific weight: 1.00 g/cm³
pH: 6 – 7
Resistance to washing: The product withstands ordinary cleaning maintenance.
Drying time: 4-6 hours according to ambient temperature and relative humidity.

Storage

Store the product in its original containers, tightly closed at ambient temperature between +5°C and +35°C, in a cool and well-ventilated place, sheltered from direct sunshine and heat sources.

Safety warnings

CEBOFLOW does not require any specific personal or environmental protection measures; it is however advised to avoid long contact with skin. In case of contact with eyes, rinse immediately with plenty of water; if irritations persist seek medical advice. If swallowed, seek medical advice immediately and show the safety data sheet of the product.

This data sheet annuls and substitutes any previous version for this product. All the technical information herein stated come from our best experience: in any case however this Technical Data Sheet does not imply the liability of our Company for application of the product which is carried out beyond our control. Our Technical Department is at the users' service to provide additional information or clarifications.