



Cebos Color Srl  
24040 Osio Sopra (BG)  
Via dei Dossi, 7  
Tel. +39 035 265141  
Fax +39 035 2651431  
C.F. & P.Iva 02567630161  
info@cebos.it  
www.ceboscolor.it

Revision No.1  
Revision date: 08/04/2022

## DATA SHEET ST B.010

### CEBOCEM Cement-based curing additive

#### Description

Cement-based curing additive for CeboRasa increases hardness and mechanical strength.

#### Packs available

2 Kg

#### Staining

Unforeseen.

#### Mixing

Using a mechanical stirrer (whisk), thoroughly mix CeboRasa with the powder additive CeboCem.

#### Dosing

CeboCem must be added to the product during stirring with a mixer drill, in the following dosages:

CeboRasa Additive CeboCem

20 Kg            1 x 2 Kg

**IMPORTANT:** Once the product has been added to CeboCem, it must be used within 1 hour.

#### Technical features

Physical appearance: Powder

Specific gravity: 1,00 g/cm<sup>3</sup>

#### VOC classification (Directive 2004/42/EC)

Product category: no category provided.

Maximum allowed (2010) no limit provided.

CeboRock contains VOC: 0 g/l

#### Storage

The product has a guaranteed duration of 12 months if stored in original packaging at temperatures between +5 and +35 °C, in a dry and ventilated place, away from the sun's rays and heat sources.

#### Safety instructions

The product needs environmental and personal protective measures; it is advisable to carefully read the label of the product before using it. The user information is contained in the relevant Safety Data Sheet.

This Data Sheet replaces and cancels all other Data Sheets relating to the product described, drawn up on the previous date. All the information in this Data Sheet derives from our best experience: however, the Data Sheet does not imply any acquisition of responsibility by our Company for applications outside our direct control. Our Technical Department is always at your disposal to provide further information or clarification.

Cebos Color Srl - decorative wall systems - tax code/VAT 02567630161