



Cebos Color Srl  
24040 Osio Sopra (BG)  
Via dei Dossi, 7  
Tel. +39 035 265141  
Fax +39 035 2651431  
C.F. & P.Iva 02567630161  
info@cebos.it  
www.ceboscolor.it

Revision No.2  
Revision date: 15/07/2019

## DATA SHEET ST C.002

### CEBOFREE BLACK

#### Description

Water-based multichromatic finish for interiors, easy to apply and extremely versatile.

#### Packs available

1 Lt - 2,5 Lt

#### Staining

The product can be stained with the CeboColorStation tintometric system or with the CeboKit universal dyes in the dosages shown on the color charts. Different colors are possible from those of the folder, varying the dosages provided and/ or mixing the dyes. Since you have to prepare several packs of the same color it is advisable to use dyes and products with the same batch of production.

#### Dilution

Unforeseen.

#### Mixing

Mix the product well before use.

CeboFree after mixing with dyes and additives should be used within 48 hours.

#### Suitable supports

All plaster, lime and civil supports are suitable. Check that the funds are perfectly clean, dry and uniform in appearance and absorption.

#### Media preparation

Apply with short hair roller FondoPlus colored diluted to 10% by volume with water, in one or two coats until the bottom is completely covered.

#### Application

After proper colouring and mixing with the chosen additive, apply CeboFree Black in a brush coat, before complete drying, go over the surface with the appropriate Caress spatula, exerting a slight pressure.

Application information is contained in videos, folders, and catalogs

#### Technical features

Drying: 6-8 h

Theoretical yield: 8 m<sup>2</sup>/litre

Physical appearance: Dense liquid, gray

Specific Weight: 1.03 g/cm<sup>3</sup>

pH: 7-8

#### VOC classification (Directive 2004/42/EC)

Product category: Decorative effect paints (I)

Maximum permitted limit (2010) for ready-to-use product 200 g/l

CeboFree contains VOC: 30 g/l

#### Storage

The product has a guaranteed duration of 12 months if stored in original packaging at temperatures between +5 and +35 °C, in a dry and ventilated place, away from the sun's rays and heat sources.

#### Safety instructions

The product does not require special environmental or personal protective measures; however it is advisable to avoid prolonged contact with the skin. In the case of eye contact immediately wash the eyes with clean water; if irritation occurs, consult a doctor. The user information is contained in the relevant Safety Data Sheet.

This Data Sheet replaces and cancels all other Data Sheets relating to the product described, drawn up on the previous date. All the information in this Data Sheet derives from our best experience: however, the Data Sheet does not imply any acquisition of responsibility by our Company for applications outside our direct control. Our Technical Department is always at your disposal to provide further information or clarification.