



Cebos Color Srl  
24040 Osio Sopra (BG)  
Via dei Dossi, 7  
Tel. +39 035 265141  
Fax +39 035 2651431  
C.F. & P.Iva 02567630161  
info@cebos.it  
www.ceboscolor.it

Revision No.2  
Revision date: 15/07/2019

## DATA SHEET ST C.006

### CEBOIRON CHROME

#### Description

Acrylic water finish for indoor and outdoor that, thanks to the special metal pigments allows you to reproduce the chrome effect on the surfaces.

#### Packs available

1 Lt – 2,5 Lt

#### Staining

The product can be stained with the CeboColorStation tintometric system or with the CeboKit universal dyes in the dosages shown on the color charts. Different colors are possible from those of the folder, varying the dosages provided and/ or mixing the dyes. Since you have to prepare several packs of the same color it is advisable to use dyes and products with the same batch of production.

#### Dilution

Unforeseen.

#### Mixing

Mix the product well before use.

#### Suitable supports

All plaster, lime and civil supports are suitable. Check that the funds are perfectly clean, dry and uniform in appearance and absorption.

#### Preparation of the supports outside

Apply with short coat roller CeboFix R white diluted to 20-30% by volume with water, in one or two coats until the bottom is completely covered. Then follow the indications of the chosen application cycle.

#### Preparation of funds within the

Apply with short hair roller FondoPlus white diluted to 10% by volume with water, in one or two coats until the bottom is completely covered. Then follow the instructions for the chosen application cycle.

#### Application

CeboIron Chrome is applied, on the bottom suitably prepared and completely dry, in two coats by brush, wait 4-6 hours between the first and the second coat.

Application information is contained in videos, folders, and catalogs.

#### Technical features

Drying: 4-6 h

Theoretical yield: 8-10 m<sup>2</sup>/litre

Physical appearance: Liquid, metallic

Specific Weight: 1.07 g/cm<sup>3</sup>

pH: 8.5-9.

#### VOC classification (Directive 2004/42/EC)

Product category: Decorative effect paints (I)

Maximum permitted limit (2010) for ready-to-use product 200 g/l

CeboIron Chrome contains VOC: 80

This Data Sheet replaces and cancels all other Data Sheets relating to the product described, drawn up on the previous date. All the information in this Data Sheet derives from our best experience: however, the Data Sheet does not imply any acquisition of responsibility by our Company for applications outside our direct control. Our Technical Department is always at your disposal to provide further information or clarification.



Cebos Color Srl  
24040 Osio Sopra (BG)  
Via dei Dossi, 7  
Tel. +39 035 265141  
Fax +39 035 2651431  
C.F. & P.Iva 02567630161  
info@cebos.it  
www.ceboscolor.it

Revision No.2  
Revision date: 09/10/2018

## DATA SHEET ST C.006

### Storage

The product has a guaranteed duration of 24 months if stored in original packaging at temperatures between +5 and +35 °C, in a dry and ventilated place, away from the sun's rays and heat sources.

### Safety instructions

The product does not require special environmental or personal protective measures; however it is advisable to avoid prolonged contact with the skin. In the case of eye contact immediately wash the eyes with clean water; if irritation occurs, consult a doctor. The user information is contained in the relevant Safety Data Sheet.

This Data Sheet replaces and cancels all other Data Sheets relating to the product described, drawn up on the previous date. All the information in this Data Sheet derives from our best experience: however, the Data Sheet does not imply any acquisition of responsibility by our Company for applications outside our direct control. Our Technical Department is always at your disposal to provide further information or clarification.

Cebos Color Srl - decorative wall systems - tax code/VAT 02567630161