Revision No.2

Revision date: 15/07/2019

DATA SHEET ST C.007

CEBOIRON GREY/BLACK

Description

Acrylic water finish for indoor and outdoor, semi-opaque, with micaceous and pearlescent pigments.

Packs available

Grey Nero1 Lt - 2,5 Lt

Staining

The product can be stained with the CeboColorStation tintometric system or with the CeboKit universal dyes in the dosages shown on the color charts. Different colors are possible from those of the folder, varying the dosages provided and/ or mixing the dyes. Since you have to prepare several packs of the same color it is advisable to use dyes and products with the same batch of production.

Dilution

Unforeseen.

Mixing

Mix the product well before use.

Suitable supports

All plaster, lime and civil supports are suitable. Check that the funds are perfectly clean, dry and uniform in appearance and absorption.

Media preparation

CeboIron can be used on different products of the Cebos color line, to know the correct preparation of the support refer to the application cycle of the desired effect.

Application

Depending on the chosen effect, CeboIron can be applied with steel or synthetic sponge, in one or two coats, wait 4-6 hours between the first and second coats

Application information is contained in videos, folders, and catalogs.

Technical features

Drying: 4-6 h

Theoretical yield: 10-15 m2^{/litre} Physical appearance: Liquid, grey

Specific Weight: Grey 1,10 g/cm3 Black 1 ,23 g/cm3

pH: 8.5-9.5

VOC classification (Directive 2004/42/EC) Product category: Decorative effect paints (1)

Maximum permitted limit (2010) for ready-to-use product 200 g/l

CeboIron Grey/Black contains VOC: 32 g/l

Storage

The product has a guaranteed duration of 24 months if stored in original packaging at temperatures between +5 and +35 °C, in a dry and ventilated place, away from the sun's rays and heat sources.

Safety instructions

The product does not require special environmental or personal protective measures; however it is advisable to avoid prolonged contact with the skin. In the case of eye contact immediately wash the eyes with clean water; if irritation occurs, consult a doctor. The user information is contained in the relevant Safety Data Sheet.

This Data Sheet replaces and cancels all other Data Sheets relating to the product described, drawn up on the previous date. All the information in this Data Sheet derives from our best experience: however, the Data Sheet does not imply any acquisition of responsibility by our Company for applications outside our direct control. Our Technical Department is always at your disposal to provide further information or clarification.