Revision No.2

Revision date: 15/07/2019

# **DATA SHEET ST C.010**

## **CEBOSI DECORO**

# Description

Water-based acrylic putty for indoor use, washable, enriched with precious metal pigments. It allows to realize elegant decorations with particular reflections typical of gold and silver.

#### Packs available

Silver, Venetian Gold, Pure Gold: 1 Lt - 3 Lt - 5 Lt

## **Staining**

The product can be stained with the CeboColorStation tintometric system or with the CeboKit universal dyes in the dosages shown on the color charts. Different colors are possible from those of the folder, varying the dosages provided and/ or mixing the dyes. Since you have to prepare several packs of the same color it is advisable to use dyes and products with the same batch of production.

## **Dilution**

Unforeseen.

#### Mixing

Mix the product well before use.

# Suitable supports

All plaster, lime and civil supports are suitable. Check that the funds are perfectly clean, dry and uniform in appearance and absorption.

# Media preparation

CeboSi Decoro can be applied on all flat and smooth surfaces. In the case of funds to civil or rustic is necessary to intervene with appropriate shaves. Apply with short hair roller CeboSi Fondo Colored, in one or two coats until the background is completely covered.

## **Application**

CeboSì Decoro is applied to in two coats with plastic or steel trowel, wait 4-6 hours between the first and the second hand

Application information is contained in videos, folders, and catalogs.

## **Technical features**

Drying: 4-6 h

Theoretical yield: 4-5 m2/litre

Physical appearance: Dense liquid, metallic

Specific Weight: 1.20-1.25 g/cm3

pH: 8.5-9.5

**VOC classification** (Directive 2004/42/EC) Product category: Decorative effect paints (1)

Maximum permitted limit (2010) for ready-to-use product 200 g/l

CeboSi Decoro contains VOC: 25 g/l

This Data Sheet replaces and cancels all other Data Sheets relating to the product described, drawn up on the previous date. All the information in this Data Sheet derives from our best experience: however, the Data Sheet does not imply any acquisition of responsibility by our Company for applications outside our direct control. Our Technical Department is always at your disposal to provide further information or clarification.



Revision No.2

Revision date: 15/07/2019

# **DATA SHEET ST C.010**

## Type of ship IAQ (indoor air quality)



Classification according to the decree of the French Republic No. 2011-321 of March 2011. Information on the level of emission of volatile substances into indoor air, which presents a risk of inhalation

toxicity, on a class scale ranging from A+ (very low) to C (very high).

#### Storage

The product has a guaranteed duration of 24 months if stored in original packaging at temperatures between +5 and +35 °C, in a dry and ventilated place, away from the sun's rays and heat sources.

#### **Safety instructions**

The product does not require special environmental or personal protective measures; however it is advisable to avoid prolonged contact with the skin. In the case of eye contact immediately wash the eyes with clean water; if irritation occurs, consult a doctor. The user information is contained in the relevant Safety Data Sheet.