



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Revision No.2
Revision date: 15/07/2019

DATA SHEET ST C.018

CEBOSTONE METAL

Description

Acrylic water-based finish for indoor, ideal for all types of wall support. CeboStone Metal allows you to easily create valuable decorations, where the sandblasted effect is enhanced by the preciousness of the metal appearance, with a succession of delicate chiaroscuro and fascinating golden reflections.

Packs available

1 Lt – 3 Lt – 5 Lt

Staining

The product can be stained with the CeboColorStation tintometric system or with the CeboKit universal dyes in the dosages shown on the color charts. Different colors are possible from those of the folder, varying the dosages provided and/ or mixing the dyes. Since you have to prepare several packs of the same color it is advisable to use dyes and products with the same batch of production.

Dilution

10% by volume with water.

Mixing

Mix the product well before use.

Suitable supports

All plaster, lime and civil supports are suitable. Check that the funds are perfectly clean, dry and uniform in appearance and absorption.

Media preparation

Apply with short hair roller FondoPlus white diluted to 10% by volume with water, in one or two coats until the surface is completely covered.

Application

CeboStone Metal is applied: diluted to 10% by volume with water, in a brush coat, working with crossed brushstrokes in order to obtain on the surface an alternation of sandy and smooth areas. Application information is contained in videos, folders, and catalogs

Technical features

Drying: 4-6 h

Theoretical yield: 7-8 m²/litre

Physical appearance: Liquid, metallic

Specific Weight: 1.46 g/cm³

pH: 8.5-9.5

VOC classification (Directive 2004/42/EC)

Product category: Decorative effect paints (I)

Maximum permitted limit (2010) for ready-to-use product 200 g/l

CeboStone Metal contains VOC: 40 g/l

This Data Sheet replaces and cancels all other Data Sheets relating to the product described, drawn up on the previous date. All the information in this Data Sheet derives from our best experience: however, the Data Sheet does not imply any acquisition of responsibility by our Company for applications outside our direct control. Our Technical Department is always at your disposal to provide further information or clarification.



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Revision No.2
Revision date: 15/07/2019

DATA SHEET ST C.018

Storage

The product has a guaranteed duration of 24 months if stored in original packaging at temperatures between +5 and +35 °C, in a dry and ventilated place, away from the sun's rays and heat sources.

Safety instructions

The product does not require special environmental or personal protective measures; however it is advisable to avoid prolonged contact with the skin. In the case of eye contact immediately wash the eyes with clean water; if irritation occurs, consult a doctor. The user information is contained in the relevant Safety Data Sheet.

This Data Sheet replaces and cancels all other Data Sheets relating to the product described, drawn up on the previous date. All the information in this Data Sheet derives from our best experience: however, the Data Sheet does not imply any acquisition of responsibility by our Company for applications outside our direct control. Our Technical Department is always at your disposal to provide further information or clarification.

Cebos Color Srl - sistemi decorativi murali - codice fiscale/partita iva 02567630161