



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Revision No.2
Revision date: 03/15/2021

DATA SHEET ST C. 025

CEBOWAX

Description

Water-based interior finish based on natural beeswax and selected binders, breathable and water-repellent.

Packs available

1 L – 2,5 L

Staining

The product can be stained with the CeboColorStation tintometric system or with the CeboKit universal dyes in the dosages shown on the color charts. Different colors are possible from those of the folder, varying the dosages provided and/ or mixing the dyes. Since you have to prepare several packs of the same color it is advisable to use dyes and products with the same batch of production.

Dilution

30 to 100% by volume with water.

Mixing

Mix the product well both before and during use.

Suitable supports

All plaster, lime and civil supports are suitable. Check that the funds are perfectly clean, dry and uniform in appearance and absorption.

Media preparation

CeboWax can be applied on different finishes of the Cebos color line for a correct preparation of the support refer to the data sheet of the product used for the realization of the chosen effect.

Application

CeboWax is applied with synthetic sponge in one or two coats.

Application information is contained in videos, application cards, folders, and catalogs.

Technical features

Drying time: 24 h

Theoretical yield: 12-14 m²/litre

Physical appearance: White liquid

Specific Weight: 1 g/cm³

pH: 7.5-8.5

VOC classification (Directive 2004/42/EC)

Product category: Decorative effect paints (I)

Maximum permitted limit (2010) for ready-to-use product 200 g/l

CeboWax contains VOC: 3 g/l

Storage

The product has a guaranteed duration of 24 months if stored in original packaging at temperatures between +5 and +35 °C, in a dry and ventilated place, away from the sun's rays and heat sources.

Safety instructions

The product does not require special environmental or personal protective measures; however it is advisable to avoid prolonged contact with the skin. In the case of eye contact immediately wash the eyes with clean water; if irritation occurs, consult a doctor. The user information is contained in the relevant Safety Data Sheet.

This Data Sheet replaces and cancels all other Data Sheets relating to the product described, drawn up on the previous date. All the information in this Data Sheet derives from our best experience: however, the Data Sheet does not imply any acquisition of responsibility by our Company for applications outside our direct control. Our Technical Department is always at your disposal to provide further information or clarification.