



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Revision No.1
Revision date: 02/19/2021

DATA SHEET ST C. 027

CeboMarmo

Description

CeboMarmo: High-quality acrylic water-based finish for interiors, with a glossy appearance. CeboMarmo reinterprets the marble effect reproducing the movements of the typical veins and the brilliance of a precious and refined material, giving an exclusive charm to every environment.

Packs available

1,2 Lt – 4,8 Lt – 12 Lt

Staining

The product can be stained with the CeboColorStation tintometric system or with the CeboKit universal dyes in the dosages shown on the color charts. Different colors are possible from those of the folder, varying the dosages provided and/ or mixing the dyes. Since you have to prepare several packs of the same color it is advisable to use dyes and products with the same batch of production.

Dilution

Unforeseen.

Mixing

Mix the product well before use.

Suitable supports

All plaster, lime and civil supports are suitable. Check that the funds are perfectly clean, dry and uniform in appearance and absorption.

Media preparation

CeboMarmo allows, thanks to its characteristics of finesse and transparency, the creation of extremely shiny marble effects; therefore requires a careful evaluation of the support, which must be, to the sight and touch, perfectly smooth and glide any imperfection must be eliminated. Failure to do so during the CeboMarmo application may result in media defects.

If it becomes necessary to shave the support, it is recommended to proceed respecting the direction and mode of application of the chosen effect.

In the presence of shaving, crumbling or absorbent primers, apply a coat of insulating fixative CeboFix M diluted 1:1 by volume with water.

Preparation of the fund

Before applying CeboMarmo it is necessary to prepare the surface with CeboFix Primo: white pigmented primer, for interiors, based on acrylic resins; suitable for application on plaster, plasterboard or with previous paints. CeboFix Primo is applied in one or two coats, until the surface is completely covered with a short coat roller diluted to 20% by volume with water.

Application

CeboMarmo is applied with steel trowel in two or more coats depending on the chosen effect.

Application information is contained in videos, application cards, folders, and catalogs.

This Data Sheet replaces and cancels all other Data Sheets relating to the product described, drawn up on the previous date. All the information in this Data Sheet derives from our best experience: however, the Data Sheet does not imply any acquisition of responsibility by our Company for applications outside our direct control. Our Technical Department is always at your disposal to provide further information or clarification.



Cebos Color Srl
24040 Osio Sopra (BG)
Via dei Dossi, 7
Tel. +39 035 265141
Fax +39 035 2651431
C.F. & P.Iva 02567630161
info@cebos.it
www.ceboscolor.it

Revision No.1
Revision date: 02/19/2021

DATA SHEET ST C. 027

Technical features

Drying: 6-8 h

Theoretical yield: 4-5 m²/litre

Physical appearance: Pasta Bianca

Specific Weight: 1.78 g/cm³

pH: 9.1-9.5

VOC classification (Directive 2004/42/EC)

Product category: Decorative effect paints (I)

Maximum permitted limit (2010) for ready-to-use product 200 g/l

CeboMarmo contains VOC: 96 g

Storage

The product has a guaranteed duration of 24 months if stored in original packaging at temperatures between +5 and +35 °C, in a dry and ventilated place, away from the sun's rays and heat sources.

Safety instructions

The product does not require special environmental or personal protective measures; however it is advisable to avoid prolonged contact with the skin. In the case of eye contact immediately wash the eyes with clean water; if irritation occurs, consult a doctor. The user information is contained in the relevant Safety Data Sheet.

This Data Sheet replaces and cancels all other Data Sheets relating to the product described, drawn up on the previous date. All the information in this Data Sheet derives from our best experience: however, the Data Sheet does not imply any acquisition of responsibility by our Company for applications outside our direct control. Our Technical Department is always at your disposal to provide further information or clarification.